

Technical sheet :


M-X 50-4



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		M-X 50-4	M-X 50-4
1.3	Power source		Diesel	Diesel
1.4	Operator type		Seated	Seated
1.5	Max. capacity	Q	5000 kg	11023 lb
1.6	Load center of gravity	c	600 mm	24 in
1.8	Load distance, centre of drive axle to fork	x	762 mm	30 in
1.9	Wheelbase	y	2120 mm	83 in
	Weight			
2.1	Service weight		7660 kg	16887 lb
2.2	Weight on front axle (laden) / rear axle (laden)		10800 kg / 1869 kg	23810 lb / 4120 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		2570 kg / 5090 kg	5666 lb / 11222 lb
	Wheels			
3.1	Tires type		Pneumatic	Pneumatic
3.3	Dimensions of rear wheels		340/80R18 XMCL 143A8	340/80R18 XMCL 143A8
3.5	Number of front wheels / rear wheels		2 / 2	2 / 2
3.5.2	Number of drive wheels		4	4
3.6	Front wheel gauge	b10	1620 mm	64 in
	Dimensions			
4.7	Height of overhead guard (cabin)	h6	2495 mm	98 in
4.19	Overall length	l1	4945 mm	195 in
4.20	Length to face of forks	l2	3745 mm	147 in
4.21	Overall width	b1	2080 mm	82 in
4.22	Forks section x width x length	s / e / l	50 mm x 150 mm / 1200 mm	2 in x 6 in / 47 in
4.23	Fork carriage ISO 2328 (class/form) A/B		4A	4A
4.24	Fork carriage width	b3	1670 mm	66 in
4.31	Ground clearance below mast	m1	265 mm	10 in
4.32	Ground clearance at centre of wheelbase	m2	375 mm	15 in
4.35	Turning radius	Wa	4155 mm	164 in
	Performances			
5.1	Travel speed (laden / unladen)		24 km/h / 23.40 km/h	15 mph / 15 mph
5.2	Lifting speed (laden / unladen)		0.40 m/s / 0.50 m/s	1 ft/s / 2 ft/s
5.3	Lowering speed (laden / unladen)		0.40 m/s / 0.40 m/s	1 ft/s / 1 ft/s
5.5	Drawbar pull (Laden / Unladen)		10360 daN / 6205 daN	10360 daN / 6205 daN
5.10	Service brake		Hydraulic	Hydraulic
	Engine			
7.1	Engine brand / model		Perkins / 1104D-44T NL38894	Perkins / 1104D-44T NL38894
7.3	Rated speed		2360 rpm	2360 rpm
	Miscellaneous			
8.1	Type of drive control		Hydraulic	Hydraulic

M-X 50-4 - Dimensional drawing



[illegible]



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes