Technical sheet :


MI 15 G



MANITOU
HANDLING YOUR WORLD

	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		MI 15 G	MI 15 G
1.3	Power source		Lpg	Lpg
1.4	Operator type		Sitting	Sitting
1.5	Max. capacity	Q	1500 kg	3307 lb
1.6	Load center of gravity	c	500 mm	20 in
1.8	Load distance, centre of drive axle to fork	x	405 mm	16 in
1.9	Wheelbase	y	1420 mm	56 in
	Weight			
2.1	Service weight		2710 kg	5975 lb
2.2	Weight on front axle (laden) / rear axle (laden)		3640 kg / 570 kg	8025 lb / 1257 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1230 kg / 1480 kg	2712 lb / 3263 lb
	Wheels			
3.1	Tires type		PPS	PPS
3.2	Dimensions of front wheels		6.50-10 10	6.50-10 10
3.3	Dimensions of rear wheels		5.00-8 8	5.00-8 8
3.5	Number of front wheels / rear wheels		2 / 2	2 / 2
3.5.2	Number of drive wheels		2	2
3.6	Front wheel gauge	b10	900 mm	35 in
3.7	Rear wheel gauge	b11	920 mm	36 in
	Dimensions			
4.7	Height of overhead guard (cabin)	h6	2090 mm	82 in
4.8	Seat height/stand height	h7	1160 mm	46 in
4.12	Height of towing bar (coupling height)	h10	315 mm	12 in
4.19	Overall length	l1	3310 mm	130 in
4.20	Length to face of forks	l2	2240 mm	88 in
4.21	Overall width	b1	1080 mm	43 in
4.21	Overall width - Single wheels	b1	1080 mm	43 in
4.22	Forks section / width / length	s / e / l	35 mm x 100 mm x 1150 mm	1 in x 4 in x 45 in
4.23	Fork carriage ISO 2328 (class/form) A/B		2A	2A
4.24	Fork carriage width	b3	1000 mm	39 in
4.31	Ground clearance below mast	m1	115 mm	5 in
4.32	Ground clearance at centre of wheelbase	m2	150 mm	6 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	3590 mm	141 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	3790 mm	149 in
4.35	Turning radius	Wa	1985 mm	78 in
4.36	Internal turning radius (over tyres)	b13	55 mm	2 in
	Performances			
5.1	Travel speed (laden / unladen)		17.50 km/h-18 km/h	11 mph-11 mph
5.2	Lifting speed (laden / unladen)		0.45 m/s-0.55 m/s	1 ft/s-2 ft/s
5.3	Lowering speed (laden / unladen)		0.50 m/s-0.55 m/s	2 ft/s-2 ft/s
5.5	Drawbar pull (Laden / Unladen)		1460 daN / 770 daN	1460 daN / 770 daN
5.7	Gradeability (laden / unladen)		20 % / 20 %	20 % / 20 %
5.10	Service brake		Hydraulic	Hydraulic
	Engine			
6.1	Drive motor rating S2 60 min		29 kW	29 kW
6.2	Lift motor rating at S3 15%		29 kW	29 kW
7.1	Engine brand / model		GCT (ex-Nissan) / K21	GCT (ex-Nissan) / K21
7.2	Engine power according to ISO 1585		29 kW	29 kW
7.3	Rated speed		2250 rpm	2250 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 2065 cm³	4 - 126 in³
	Energy consumption according to VDI cycle (Gas)		5.70 kg CO2/h	5.70 kg CO2/h
	Miscellaneous			
8.2	Working hydraulic pressure for attachments		160 bar	2321 PSI
8.3	Oil flow rate for attachments		52 l/min	14 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 81 dB	< 81 dB
8.4	Sound level at the driver's ear according to DIN 12 053		81 dB	81 dB

MI 15 G - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 33	FVD 37	FVD 40
Mast/fork carriage tilt, forward	°	6	6	6
Mast/fork carriage tilt, backward	°	12	12	12
h1 - Mast lowered height	in (mm)	84.4 (2145)	94.3 (2395)	102.2 (2595)
h2 - Mast free lift	in (mm)	6.1 (155)	6.1 (155)	6.1 (155)
h3 - Mast lifting height	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
h4 - Mast extended height	in (mm)	152.2 (3865)	167.9 (4265)	181.1 (4600)
Residual capacity at max height	lb (kg)	3307 (1500)	3307 (1500)	3307 (1500)
Residual capacity with integrated side shift at max heigth	lb (kg)	3307 (1500)	3307 (1500)	3307 (1500)
Height at max capacity	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
Height at max capacity with integrated sideshift	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)

Free Lift Duplex (FLD)		FLD 33	FLD 37	FLD 40
Mast/fork carriage tilt, forward	°	6	6	6
Mast/fork carriage tilt, backward	°	12	12	12
h1 - Mast lowered height	in (mm)	85 (2160)	92.9 (2360)	100.8 (2560)
h2 - Mast free lift	in (mm)	62 (1575)	69.9 (1775)	77.8 (1975)
h3 - Mast lifting height	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
h4 - Mast extended height	in (mm)	153 (3885)	168.7 (4285)	180.5 (4585)
Residual capacity at max height	lb (kg)	3307 (1500)	3307 (1500)	3307 (1500)
Residual capacity with integrated side shift at max heigth	lb (kg)	3307 (1500)	3307 (1500)	3307 (1500)
Height at max capacity	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
Height at max capacity with integrated sideshift	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)

Free Lift Triplex (FLT)		FLT 43	FLT 45	FLT 47	FLT 48	FLT 50	FLT 55	FLT 60	FLT 65
Mast/fork carriage tilt, forward	°	6	6	6	6	6	3	3	3
Mast/fork carriage tilt, backward	°	6	6	6	6	6	6	6	6
h1 - Mast lowered height	in (mm)	81.5 (2070)	83.5 (2120)	85.4 (2170)	87.4 (2220)	89.4 (2270)	97.2 (2470)	107.1 (2720)	113 (2870)
h2 - Mast free lift	in (mm)	55.1 (1400)	59.1 (1500)	62.4 (1585)	63 (1600)	66.3 (1685)	74.2 (1885)	82.7 (2100)	86.6 (2200)
h3 - Mast lifting height	in (mm)	169.3 (4300)	177.2 (4500)	185 (4700)	189 (4800)	196.9 (5000)	216.5 (5500)	236.2 (6000)	255.9 (6500)
h4 - Mast extended height	in (mm)	196.1 (4980)	202 (5130)	211.8 (5380)	213.8 (5430)	220.3 (5595)	240 (6095)	265 (6730)	282.7 (7180)
Residual capacity at max height	lb (kg)	2976 (1350)	2866 (1300)	2756 (1250)	2756 (1250)	2646 (1200)	2094 (950)	1543 (700)	
Residual capacity with integrated side shift at max heigth	lb (kg)	2976 (1350)	2866 (1300)	2535 (1150)	2535 (1150)	2425 (1100)	1874 (850)	1323 (600)	
Height at max capacity	in (mm)	157.5 (4000)	98.4 (2500)	98.4 (2500)	98.4 (2500)	98.4 (2500)	98.4 (2500)	98.4 (2500)	98.4 (2500)

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes