

Technical sheet :


MI 30 D



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		MI 30 D	MI 30 D
1.3	Power source		Diesel	Diesel
1.4	Operator type		Seated	Seated
1.5	Max. capacity	Q	3000 kg	6614 lb
1.6	Load center of gravity	c	500 mm	20 in
1.8	Load distance, centre of drive axle to fork	x	480 mm	19 in
1.9	Wheelbase	y	1700 mm	67 in
	Weight			
2.1	Service weight		4610 kg	10163 lb
2.2	Weight on front axle (laden) / rear axle (laden)		6650 kg / 960 kg	14661 lb / 2116 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1860 kg / 2750 kg	4101 lb / 6063 lb
	Wheels			
3.1	Tires type		Solid tires	Solid tires
3.2	Dimensions of front wheels		28-9-15 12	28-9-15 12
3.3	Dimensions of rear wheels		6.50-10 10	6.50-10 10
3.5	Number of front wheels / rear wheels		2 / 2	2 / 2
3.5.2	Number of drive wheels		2	2
3.6	Front wheel gauge	b10	1005 mm	40 in
3.7	Rear wheel gauge	b11	975 mm	38 in
	Dimensions			
4.7	Height of overhead guard (cabin)	h6	2130 mm	84 in
4.8	Seat height/stand height	h7	1215 mm	48 in
4.12	Height of towing bar (coupling height)	h10	355 mm	14 in
4.19	Overall length	l1	3875 mm	153 in
4.20	Length to face of forks	l2	2715 mm	107 in
4.21	Overall width	b1	1225 mm	48 in
4.21	Overall width - Single wheels	b1	1225 mm	48 in
4.22	Forks section / width / length	s / e / l	45 mm x 122 mm x 1150 mm	2 in x 5 in x 45 in
4.23	Fork carriage ISO 2328 (class/form) A/B		3A	3A
4.24	Fork carriage width	b3	1100 mm	43 in
4.31	Ground clearance below mast	m1	130 mm	5 in
4.32	Ground clearance at centre of wheelbase	m2	200 mm	8 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	4140 mm	163 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	4340 mm	171 in
4.35	Turning radius	Wa	2460 mm	97 in
4.36	Internal turning radius (over tyres)	b13	160 mm	6 in
	Performances			
5.1	Travel speed (laden / unladen)		18 km/h-18.50 km/h	11 mph-11 mph
5.2	Lifting speed (laden / unladen)		0.45 m/s-0.52 m/s	1 ft/s-2 ft/s
5.3	Lowering speed (laden / unladen)		0.43 m/s-0.48 m/s	1 ft/s-2 ft/s
5.5	Drawbar pull (Laden / Unladen)		1600 daN / 1380 daN	1600 daN / 1380 daN
5.7	Gradeability (laden / unladen)		20 % / 20 %	20 % / 20 %
5.10	Service brake		Hydraulic	Hydraulic
	Engine			
7.1	Engine brand / model		Yanmar / 4TNV94L-BXPHZ	Yanmar / 4TNV94L-BXPHZ
7.2	Engine power according to ISO 1585		35 kW	35 kW
7.3	Rated speed		2400 rpm	2400 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 3054 cm³	4 - 186 in³
	Miscellaneous			
8.2	Working hydraulic pressure for attachments		160 bar	2321 PSI
8.3	Oil flow rate for attachments		69 l/min	18 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 84 dB	< 84 dB
8.4	Sound level at the driver's ear according to DIN 12 053		84 dB	84 dB

MI 30 D - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 33	FVD 37	FVD 40
Mast/fork carriage tilt, forward	°	6	6	6
Mast/fork carriage tilt, backward	°	12	12	12
h1 - Mast lowered height	in (mm)	86.6 (2200)	96.5 (2450)	104.3 (2650)
h2 - Mast free lift	in (mm)	5.7 (145)	5.7 (145)	5.7 (145)
h3 - Mast lifting height	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
h4 - Mast extended height	in (mm)	158.9 (4035)	174.6 (4435)	186.4 (4735)
Residual capacity at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)
Residual capacity with integrated side shift at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)
Height at max capacity	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
Height at max capacity with integrated sideshift	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)

Free Lift Duplex (FLD)		FLD 33	FLD 37	FLD 40
Mast/fork carriage tilt, forward	°	6	6	6
Mast/fork carriage tilt, backward	°	12	12	12
h1 - Mast lowered height	in (mm)	87.8 (2230)	95.7 (2430)	101.6 (2580)
h2 - Mast free lift	in (mm)	58.1 (1475)	65.9 (1675)	71.9 (1825)
h3 - Mast lifting height	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
h4 - Mast extended height	in (mm)	159.6 (4055)	175.4 (4455)	187.2 (4755)
Residual capacity at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)
Residual capacity with integrated side shift at max height	lb (kg)	6614 (3000)	6614 (3000)	6614 (3000)
Height at max capacity	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)
Height at max capacity with integrated sideshift	in (mm)	129.9 (3300)	145.7 (3700)	157.5 (4000)

Free Lift Triplex (FLT)		FLT 43	FLT 45	FLT 47	FLT 48	FLT 50	FLT 55	FLT 60	FLT 65
Mast/fork carriage tilt, forward	°	6	6	6	6	6	3	3	3
Mast/fork carriage tilt, backward	°	6	6	6	6	6	6	6	6
h1 - Mast lowered height	in (mm)	83.3 (2115)	85.2 (2165)	87.2 (2215)	89.2 (2265)	91.1 (2315)	99 (2515)	108.9 (2765)	114.8 (2915)
h2 - Mast free lift	in (mm)	53.5 (1360)	55.5 (1410)	57.5 (1460)	59.4 (1510)	61.4 (1560)	69.3 (1760)	79.1 (2010)	85 (2160)
h3 - Mast lifting height	in (mm)	169.3 (4300)	177.2 (4500)	185 (4700)	189 (4800)	196.9 (5000)	216.5 (5500)	236.2 (6000)	255.9 (6500)
h4 - Mast extended height	in (mm)	199 (5055)	208.9 (5305)	214.8 (5455)	218.7 (5555)	226.6 (5755)	246.3 (6255)	267.9 (6805)	285.6 (7255)
Residual capacity at max height	lb (kg)	6504 (2950)	6393 (2900)	6173 (2800)	6173 (2800)	5512 (2500)	4079 (1850)	3086 (1400)	2866 (1300)
Residual capacity with integrated side shift at max height	lb (kg)	6283 (2850)	6173 (2800)	5952 (2700)	5952 (2700)	5291 (2400)	3858 (1750)	2866 (1300)	2756 (1250)
Height at max capacity	in (mm)	157.5 (4000)	157.5 (4000)	157.5 (4000)	157.5 (4000)	157.5 (4000)	157.5 (4000)	157.5 (4000)	98.4 (2500)
Height at max capacity with integrated sideshift	in (mm)	157.5 (4000)	157.5 (4000)	157.5 (4000)	157.5 (4000)				



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes