

Technical sheet :

# **MLT 845-100 H**



---



 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Metric	Imperial
Max. capacity	Q	4500 kg	9921 lb
Max. lifting height	h3	7.55 m	24 ft 9 in
Max. outreach		4.57 m	15 ft
Reach at max. height		1.55 m	5 ft 1 in
Breakout force with bucket		6650 daN	6650 daN
Weight and dimensions			
Unladen weight (with forks)		9080 kg	20018 lb
Ground clearance	m4	0.45 m	1 ft 6 in
Wheelbase	y	2.77 m	9 ft 1 in
Overall length to carriage (with hitch)	l11	5.22 m	17 ft 2 in
Front overhang		1.39 m	4 ft 7 in
Overall width	b1	2.42 m	7 ft 11 in
Overall cab width	b4	0.95 m	3 ft 1 in
Overall height	h17	2.58 m	8 ft 6 in
Tilt-down angle	a5	130 °	130 °
Tilt-up angle	a4	12 °	12 °
External turning radius (over tyres)	Wa1	4.18 m	13 ft 9 in
Standard tires		Alliance - A580 - 460/70 R24 159A8	Alliance - A580 - 460/70 R24 159A8
Drive wheels (front / rear)		2 / 2	2 / 2
Steering wheels (front / rear)		2 / 2	2 / 2
Performances			
Lifting		10 s	10 s
Lowering		6.50 s	6.50 s
Extension		12 s	12 s
Retraction		9.50 s	9.50 s
Crowd		4 s	4 s
Dump		3 s	3 s
Engine			
Engine brand		Deutz	Deutz
Engine norm		Stage IV	Stage IV
Engine model		TCD 3.6 l	TCD 3.6 l
Number of cylinders - Capacity of cylinders		4 - 3600 cm³	4 - 220 in³
I.C. Engine power rating / Power		101 Hp / 74.40 kW	101 Hp / 74.40 kW
Max. torque / Engine rotation		410 Nm @1600 rpm	302 ft/lbs @1600 rpm
Drawbar pull (Laden)		8460 daN	8460 daN
Reversible fan		Standard	Standard
Engine cooling system		3 radiators water + intercooler + hydraulic oil	3 radiators water + intercooler + hydraulic oil
Transmission			
Transmission type		Hydrostatic	Hydrostatic
Max. travel speed (may vary according to applicable regulations)		28 km/h	17 mph
Differential lock		Limited slip differential on front axle	Limited slip differential on front axle
Parking brake		Automatic negative parking brake	Automatic negative parking brake
Service brake		Oil-immersed multi-discs on front & rear axles	Oil-immersed multi-discs on front & rear axles
Hydraulics			
Hydraulic pump type		Variable displacement pump	Variable displacement pump
Hydraulic flow - Pressure		150 l/min - 270 bar	40 US gpm - 3916 PSI
Flow sharing distributor		Standard	Standard
Tank capacities			
Hydraulic oil		131 l	35 US gal
Fuel tank		135 l	36 US gal
Diesel Exhaust fluid (AdBlue® type)		10 l	3 US gal
Noise and vibration			
Noise at driving position (LpA) tested following NF EN 12053 norm		79 dB	79 dB
Noise to environment (LwA)		103 dB	103 dB
Vibration to whole hand/arm		< 2.50 m/s²	< 2.50 m/s²
Miscellaneous			
Tractor homologation			
Safety cab homologation		ROPS - FOPS level 2 cab	ROPS - FOPS level 2 cab
Controls		JSM	JSM

# MLT 845-100 H - Dimensional drawing





**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes