Technical sheet :

MLT-X 625-75 H




MANITOU
HANDLING YOUR WORLD


Capacities		Metric	Imperial
Max. capacity	Q	2500 kg	5512 lb
Max. lifting height	h3	5.90 m	19 ft 4 in
Max. outreach		3.30 m	10 ft 10 in
Reach at max. height		0.50 m	1 ft 8 in
Breakout force with bucket		4205 daN	4205 daN
Weight and dimensions			
Unladen weight (with forks)		4922 kg	10851 lb
Ground clearance	m4	0.38 m	1 ft 3 in
Wheelbase	y	2.30 m	7 ft 7 in
Overall length to carriage (with hitch)	l11	3.90 m	12 ft 10 in
Overall length to carriage (without hitch)	l3	3.90 m	12 ft 10 in
Front overhang		0.99 m	3 ft 3 in
Overall width	b1	1.81 m	5 ft 11 in
Overall cab width	b4	0.80 m	2 ft 7 in
Overall height	h17	2 m	6 ft 7 in
Tilt-down angle	a5	117 °	117 °
Tilt-up angle	a4	12 °	12 °
External turning radius (over tyres)	Wa1	3.31 m	10 ft 10 in
Standard tires		Alliance - A580 - 300/75 R18 142A8	Alliance - A580 - 300/75 R18 142A8
Drive wheels (front / rear)		2 / 2	2 / 2
Steering wheels (front / rear)		2 / 2	2 / 2
Performances			
Lifting		7.30 s	7.30 s
Lowering		4.95 s	4.95 s
Extension		5.20 s	5.20 s
Retraction		3.70 s	3.70 s
Crowd		3.20 s	3.20 s
Dump		3.20 s	3.20 s
Engine			
Engine brand		Kubota	Kubota
Engine norm		Stage IIIA	Stage IIIA
Max. fuel sulphur content		500 ppm	500 ppm
Engine model		V3307-DI-T-E3B	V3307-DI-T-E3B
Number of cylinders - Capacity of cylinders		4 - 3331 cm³	4 - 203 in³
I.C. Engine power rating / Power		75 Hp / 55.40 kW	75 Hp / 55.40 kW
Max. torque / Engine rotation		265 Nm @1400 rpm	195 ft/lbs @1400 rpm
Reversible fan		Standard	Standard
Engine cooling system		Engine Cooling 2 radiators (water + hydraulic oil)	Engine Cooling 2 radiators (water + hydraulic oil)
Transmission			
Transmission type		Hydrostatic	Hydrostatic
Number of gears (forward / reverse)		2 / 2	2 / 2
Max. travel speed (may vary according to applicable regulations)		25 km/h	16 mph
Differential lock		Limited slip differential on front axle	Limited slip differential on front axle
Parking brake		Automatic Negative Hand-brake	Automatic Negative Hand-brake
Service brake		Oil-Immersed multi-discs braking on front axles	Oil-Immersed multi-discs braking on front axles
Hydraulics			
Hydraulic pump type		Gear pump	Gear pump
Hydraulic flow - Pressure		86 l/min - 235 bar	23 US gpm - 3408 PSI
Tank capacities			
Hydraulic oil		115 l	30 US gal
Fuel tank		63 l	17 US gal
Noise and vibration			
Noise at driving position (LpA) tested following NF EN 12053 norm		76 dB	76 dB
Environmental noise (LwA)		104 dB	104 dB
Vibration to whole hand/arm		< 2.50 m/s²	< 2.50 m/s²
Miscellaneous			
Tractor homologation			
Safety cab homologation		ROPS - FOPS level 1 cab	ROPS - FOPS level 1 cab
Controls		JSM	JSM


Optional tires tab

Optional tires	Overall height	Overall width
BKT - AS504 - 15/55-17 122A8	6 ft 6 in (1.99 m)	6 ft 4 in (1.93 m)
ALLIANCE - A328 - 400/55 R17.5 149A8	6 ft 7 in (2.01 m)	6 ft 4 in (1.92 m)
MICHELIN - XMCL - 280/80 R18 132A8	6 ft 7 in (2.01 m)	6 ft (1.82 m)
MICHELIN - XMCL - 280/80 R20 133A8	6 ft 8 in (2.03 m)	5 ft 10 in (1.79 m)

MLT-X 625-75 H - Dimensional drawing







Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes