

Technical sheet :

EMA II 20 HD-1



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics		Metric		Imperial	
1.1	Manufacturer		Manitou		Manitou
1.2	Model Name		EMA II 20 HD-1		EMA II 20 HD-1
1.3	Power source		Electrical		Electrical
1.4	Operator type		Seated		Seated
1.5	Max. capacity	Q	2000 kg		4409 lb
1.6	Load center of gravity	c	500 mm		20 in
1.8	Load distance, centre of drive axle to fork	x	278 mm		11 in
1.9	Wheelbase	y	1745 mm		69 in
Weight					
2.1	Service weight		6900 kg		15212 lb
2.2	Weight on front axle (laden) / rear axle (laden)		4200 kg / 4500 kg		9259 lb / 9921 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		2200 kg / 4700 kg		4850 lb / 10362 lb
Wheels					
3.1	Tires type		Solid tires		Solid tires
3.2	Dimensions of front wheels		412 x 178		412 x 178
3.3	Dimensions of rear wheels		457 x 178		457 x 178
3.5	Number of front wheels / rear wheels		2 / 2		2 / 2
3.5.2	Number of drive wheels		2		2
3.6	Front wheel gauge	b10	1110 mm		44 in
3.7	Rear wheel gauge	b11	1250 mm		49 in
Dimensions					
4.7	Height of overhead guard (cabin)	h6	2260 mm		89 in
4.8	Seat height/stand height	h7	1200 mm		47 in
4.19	Overall length	l1	3710 mm		146 in
4.20	Length to face of forks	l2	2560 mm		101 in
4.21	Overall width	b1	1250 mm		49 in
4.22	Forks section / width / length	s / e / l	40 mm x 125 mm x 1150 mm		2 in x 5 in x 45 in
4.23	Fork carriage ISO 2328 (class/form) A/B		2		2
4.24	Fork carriage width	b3	860 mm		34 in
4.31	Ground clearance below mast	m1	50 mm		2 in
4.32	Ground clearance at centre of wheelbase	m2	130 mm		5 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	1950 mm		77 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2150 mm		85 in
Performances					
5.1	Travel speed (laden / unladen)		9 km/h-9.50 km/h		6 mph-6 mph
5.2	Lifting speed (laden / unladen)		0.35 m/s-0.45 m/s		1 ft/s-1 ft/s
5.3	Lowering speed (laden / unladen)		0.40 m/s-0.36 m/s		1 ft/s-1 ft/s
5.7	Gradeability (laden / unladen)		8 % / 10.50 %		8 % / 10.50 %
5.10	Service brake		Hydraulic		Hydraulic
Engine					
6.1	Drive motor rating S2 60 min		10 kW		10 kW
6.2	Lift motor rating at S3 15%		9 kW		9 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN 43595		DIN 43595
6.4	Battery voltage / capacity		48 V / 775 Ah		48 V / 775 Ah
6.5	Battery weight (+/- 5%)		1435 kg		3164 lb
Miscellaneous					
8.1	Type of drive control		Mosfet AC speed controller		Mosfet AC speed controller
8.2	Working hydraulic pressure for attachments		200 bar		2901 PSI
8.3	Oil flow rate for attachments		25 l/min		7 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 73 dB		< 73 dB
8.4	Sound level at the driver's ear according to DIN 12 053		73 dB		73 dB

EMA II 20 HD-1 - Dimensional drawing



Characteristics of masts and residual capacities

Free Lift Triplex (FLT)		FLT 56	FLT 60	FLT 66	FLT 70	FLT 76	FLT 80	FLT 86	FLT 90	FLT 95	FLT 102	FLT 106
Mast/fork carriage tilt, forward	°	1	1	1	1	1	1	1	1	1	1	1
Mast/fork carriage tilt, backward	°	3	3	3	3	3	3	3	3	3	3	3
h1 - Mast lowered height	in (mm)	108.3 (2750)	114.2 (2900)	124 (3150)	129.5 (3290)	141.3 (3590)	146.5 (3720)	158.3 (4020)	163.4 (4150)	177.2 (4500)	184.6 (4690)	189.8 (4820)
h2 - Mast free lift	in (mm)	76 (1930)	81.9 (2080)	91.7 (2330)	97.2 (2470)	109.1 (2770)	114.2 (2900)	126 (3200)	131.1 (3330)	143.7 (3650)	152.4 (3870)	157.5 (4000)
h3 - Mast lifting height	in (mm)	218.5 (5550)	236.2 (6000)	259.8 (6600)	276.4 (7020)	300 (7620)	315.4 (8010)	339 (8610)	354.3 (9000)	374 (9500)	401.6 (10200)	415.7 (10560)
h4 - Mast extended height	in (mm)	251.2 (6380)	268.9 (6830)	292.5 (7430)	309.1 (7850)	332.7 (8450)	348 (8840)	371.7 (9440)	387 (9830)	412.4 (10475)	440 (11175)	454.1 (11535)
Residual capacity with integrated side shift at max heigh	lb (kg)	3527 (1600)	3197 (1450)	3197 (1450)	2866 (1300)	2866 (1300)	2646 (1200)	2425 (1100)	2205 (1000)	1984 (900)	1653 (750)	1433 (650)



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes