

Technical sheet :

# 140 SC

---




 **MANITOU**  
HANDLING YOUR WORLD

| Capacities                                   |         | Metric   | Imperial   |
|--|---------|--|--|
| Working height                               | h21     | 14.20 m  | 46 ft 7 in   |
| Platform height                              | h7      | 12.20 m  | 40 ft  |
| Platform capacity                            | Q       | 363 kg   | 800 lb   |
| Max. capacity on the extension deck          |         | 136 kg   | 300 lb   |
| Number of people (indoor / outdoor)          |         | 3 / 2  | 3 / 2  |
| Weight and dimensions                        |         |  |  |
| Platform weight*                             |         | 5215 kg  | 11497 lb   |
| Platform dimensions (length x width)         | lp / ep | 2.79 m x 1.60 m  | 9 ft 2 in x 5 ft 3 in  |
| Platform dimensions with extension (length)  |         | 4.31 m   | 14 ft 2 in   |
| Overall length                               | l1      | 3.76 m   | 12 ft 4 in   |
| Overall width                                | b1      | 1.75 m   | 5 ft 9 in  |
| Overall height                               | h17     | 2.74 m   | 9 ft   |
| Overall height (stowed) **                   | h18     | 2.08 m   | 6 ft 10 in   |
| External turning radius                      | Wa3     | 4.60 m   | 15 ft 1 in   |
| Ground clearance at centre of wheelbase      | m2      | 0.24 m   | 9 in   |
| Wheelbase                                    | y       | 2.29 m   | 7 ft 6 in  |
| Performances                                 |         |  |  |
| Drive speed - stowed                         |         | 5.60 km/h  | 3 mph  |
| Drive speed - raised                         |         | 0.40 km/h  | 0.25 mph   |
| Raise speed (laden) / Lower speed (laden)    |         | 69 s / 46 s  | 69 s / 46 s  |
| Gradeability                                 |         | 30 %   | 30 %   |
| Max outrigger leveling side to side          |         | 11.70 °  | 11.70 °  |
| Permissible leveling (front / side)          |         | 3 ° / 2 °  | 3 ° / 2 °  |
| Wheels                                       |         |  |  |
| Tires type                                   |         | Foam-filled  | Foam-filled  |
| Drive wheels (front / rear)                  |         | 2 / 2  | 2 / 2  |
| Steering wheels (front / rear)               |         | 2 / 0  | 2 / 0  |
| Braking wheels (front / rear)                |         | 2 / 2  | 2 / 2  |
| Engine/Battery                               |         |  |  |
| Engine brand / model                         |         | Kubota - D1105   | Kubota - D1105   |
| Engine nom                                   |         | Tier 4 final   | Tier 4 final   |
| I.C. Engine power rating / Power             |         | 25 Hp / 18.50 kW   | 25 Hp / 18.50 kW   |
| Miscellaneous                                |         |  |  |
| Ground Pressure                              |         | 6.68 dan/cm2   | 97 PSI   |
| Hydraulic tank capacity                      |         | 68.10 l  | 18 US gal  |
| Fuel tank                                    |         | 37.90 l  | 10 US gal  |
| Sound pressure level (platform work station) |         | 79 dB  | 79 dB  |
| Noise to environment (LwA)                   |         | < 85 dB  | < 85 dB  |
| Vibration on hands/arms                      |         | < 2.50 m/s²  | < 2.50 m/s²  |
| Standards compliance                         |         |  |  |
| This machine is in compliance with:          |         | European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage) | European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage) |

\*\* With folded guardrail

140 SC - Load chart



140 SC - Dimensional drawing



Equipment

| Standard  |
|---|
| 230V Predisposition   |
| 4 wheel drive   |
| Anti-slip platform surface  |
| Audible alarm and illuminated indicator lamp (leveling, overload, lowering) |
| CAN bus technology  |
| Emergency stop button in platform and on frame                              |
| Engine mounted on sliding platform  |
| Fixed anti-shearing protection  |
| Folding rails with half height swing gate                                   |
| Hom in the platform   |
| Hour meter  |
| Integrated diagnostic assistance  |
| Lowering alarm  |
| Oscillating front axle  |
| Platform access gate  |
| Proportional controls   |
| Removable control unit  |
| Stabilizers with automatic leveling   |
| Travel possible at maximum height   |
| Optional  |
| 2 flashing lights on frame  |
| Biodegradable oil   |
| Lights  |
| Non-marking tyres   |
| Safety harness  |
| Working headlight in platform   |

**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes