

Technical sheet :


ES-C 507



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		ES 507 GPF - ES-C 507	ES 507 GPF - ES-C 507
1.3	Power source		Electrical	Electrical
1.4	Operator type		Pedestrian	Pedestrian
1.5	Max. capacity	Q	700 kg	1543 lb
1.6	Load center of gravity	c	400 mm	16 in
1.8	Distance from Load backrest to center of rear axle	x	101 mm	4 in
1.9	Wheelbase	y	932 mm	37 in
	Weight			
2.1	Service weight		1250 kg	2756 lb
2.2	Weight on front axle (laden) / rear axle (laden)		1893 kg / 307 kg	4173 lb / 677 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		820 kg / 680 kg	1808 lb / 1499 lb
	Wheels			
3.1	Tires type		Polyurethane	Polyurethane
3.3	Number of load wheels / Size of load wheels		2 / 150x70	2 / 150x70
3.5	Number of front wheels / rear wheels		1 / 2	1 / 2
3.5.2	Number of drive wheels / Size of drive wheels		1/230x70	1/230x70
3.7	Rear wheel gauge	b11	826 mm	33 in
	Dimensions			
4.15	Fork height in low position	h13	35 mm	1 in
4.19	Overall length	l1	2013 mm	79 in
4.20	Length to face of forks	l2	1213 mm	48 in
4.21	Overall width	b1	923 mm	36 in
4.22	Forks section / width / length	s / e / l	30 mm / 90 mm / 800 mm	1 in / 4 in / 31 in
4.23	Fork carriage ISO 2328 (class/form) A/B		2B	2B
4.24	Fork carriage width	b3	750 mm	30 in
4.31	Ground clearance below mast	m1	60 mm	2 in
4.32	Ground clearance at centre of wheelbase	m2	69 mm	3 in
4.35	Turning radius	Wa	1335 mm	53 in
4.9	Height tiller min. / max.	h14 / h14	830 mm / 1385 mm	33 in / 55 in
	Performances			
5.1	Travel speed (laden / unladen)		4.50 km/h / 4.50 km/h	3 mph / 3 mph
5.2	Lifting speed (laden / unladen)		0.30 m/s / 0.18 m/s	0.98 ft/s / 0.59 ft/s
5.3	Lowering speed (laden / unladen)		0.22 m/s / 0.27 m/s	0.72 ft/s / 0.89 ft/s
5.8	Max Gradeability (laden / unladen)		7 % / 10 %	7 % / 10 %
5.10	Service brake		Electro magnetic	Electro magnetic
	Engine			
6.1	Drive motor rating S2 60 min		1.50 kW	1.50 kW
6.2	Lift motor rating at S3 15%		3 kW	3 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN 43535-B	DIN 43535-B
6.4	Battery voltage / capacity		24 V / 180 Ah	24 V / 180 Ah
6.5	Battery weight (+/- 5%)		189 kg	417 lb
	Miscellaneous			
8.1	Type of drive control		AC	AC
8.4	Sound level at the driver's ear according to DIN 12 053		65 dB	65 dB

ES-C 507 - Dimensional drawing



Characteristics of masts and residual capacities

Central Cylinder Simplex (CCS)		CCS 15	CCS 17
h1 - Mast lowered height	in (mm)	76 (1931)	85.9 (2181)
h2 - Mast free lift	in (mm)	55.9 (1420)	65.7 (1670)
h3 - Mast lifting height	in (mm)	55.9 (1420)	65.7 (1670)
h4 - Mast extended height	in (mm)	81.5 (2070)	91.3 (2320)
Residual capacity at max height	lb (kg)	1543 (700)	1543 (700)

Full Visibility Duplex (FVD)		FVD 29	FVD 34	FVD 38
h1 - Mast lowered height	in (mm)	76 (1931)	85.9 (2181)	93.7 (2381)
h3 - Mast lifting height	in (mm)	112.2 (2850)	131.9 (3350)	147.6 (3750)
h4 - Mast extended height	in (mm)	137.8 (3500)	157.5 (4000)	173.2 (4400)
Residual capacity at max height	lb (kg)	1543 (700)	1543 (700)	1323 (600)

Free Lift Duplex (FLD)		FLD 29	FLD 34
h1 - Mast lowered height	in (mm)	76 (1931)	85.9 (2181)
h2 - Mast free lift	in (mm)	55.9 (1420)	65.7 (1670)
h3 - Mast lifting height	in (mm)	112.2 (2850)	132.1 (3355)
h4 - Mast extended height	in (mm)	137.8 (3500)	157.5 (4000)
Residual capacity at max height	lb (kg)	1543 (700)	1543 (700)

Free Lift Triplex (FLT)		FLT 42
h1 - Mast lowered height	in (mm)	77 (1956)
h2 - Mast free lift	in (mm)	54.3 (1380)
h3 - Mast lifting height	in (mm)	163.8 (4160)
h4 - Mast extended height	in (mm)	189.4 (4810)
Residual capacity at max height	lb (kg)	1102 (500)



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes