

Technical sheet :

# ES 612 LI

---



 **MANITOU**  
HANDLING YOUR WORLD

	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		ES 612 LI	ES 612 LI
1.3	Power source		Electrical	Electrical
1.4	Operator type		Pedestrian	Pedestrian
1.5	Max. capacity	Q	1200 kg	2646 lb
1.6	Load center of gravity	c	600 mm	24 in
1.8	Distance from Load backrest to center of rear axle	x	834 mm	33 in
1.9	Wheelbase	y	1492 mm	59 in
	Weight			
2.1	Service weight		1251 kg	2758 lb
2.2	Weight on front axle (laden) / rear axle (laden)		1295 kg / 1163 kg	2855 lb / 2564 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1328 kg / 1003 kg	2928 lb / 2211 lb
	Wheels			
3.1	Tires type		Bandage	Bandage
3.3	Number of load wheels / Size of load wheels		2 / 140x60	2 / 140x60
3.4	Number of stabilizer wheels / Size of the stabilizer wheels		1 / 140x60	1 / 140x60
3.5	Number of front wheels / rear wheels		2 / 4	2 / 4
3.5.2	Number of drive wheels / Size of drive wheels		1/230x70	1/230x70
3.6	Front wheel gauge	b10	529 mm	21 in
3.7	Rear wheel gauge	b11	380 mm	15 in
	Dimensions			
4.6	Initial lift	h5	110 mm	4 in
4.19	Overall length	l1	2162 mm	85 in
4.20	Length to face of forks	l2	973 mm	38 in
4.21	Overall width	b1	800 mm	31 in
4.22	Forks section / width / length	s / e / l	60 mm / 185 mm / 1190 mm	2 in / 7 in / 47 in
4.24	Fork carriage width	b3	700 mm	28 in
4.32	Ground clearance at centre of wheelbase	m2	30 mm	1 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	2521 mm	99 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2428 mm	96 in
4.35	Turning radius	Wa	1716 mm	68 in
4.9	Height tiller min. / max.	h14 / h14	750 mm / 1250 mm	30 in / 49 in
	Performances			
5.1	Travel speed (laden / unladen)		4.50 km/h / 4.50 km/h	3 mph / 3 mph
5.2	Lifting speed (laden / unladen)		0.18 m/s / 0.30 m/s	0.59 ft/s / 0.98 ft/s
5.3	Lowering speed (laden / unladen)		0.27 m/s / 0.22 m/s	0.89 ft/s / 0.72 ft/s
5.8	Max Gradeability (laden / unladen)		7 % / 10 %	7 % / 10 %
5.10	Service brake		Electro magnetic	Electro magnetic
	Engine			
6.1	Drive motor rating S2 60 min		1.50 kW	1.50 kW
6.2	Lift motor rating at S3 15%		3 kW	3 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN 43535-B	DIN 43535-B
6.4	Battery voltage / capacity		24 V / 180 Ah	24 V / 180 Ah
6.5	Battery weight (+/- 5%)		189 kg	417 lb
	Miscellaneous			
8.1	Type of drive control		AC	AC
8.4	Sound level at the driver's ear according to DIN 12 053		65 dB	65 dB

## ES 612 LI - Dimensional drawing



# Characteristics of masts and residual capacities

Central Cylinder Simplex (CCS)		CCS 15	CCS 17
h1 - Mast lowered height	in (mm)	76.9 (1953)	86.7 (2203)
h2 - Mast free lift	in (mm)	59.3 (1506)	69.1 (1756)
h3 - Mast lifting height	in (mm)	59.3 (1506)	69.1 (1756)
h4 - Mast extended height	in (mm)	77.2 (1960)	87 (2210)
Residual capacity at max height	lb (kg)	2646 (1200)	2646 (1200)

Full Visibility Duplex (FVD)		FVD 29	FVD 34	FVD 38
h1 - Mast lowered height	in (mm)	76.9 (1953)	86.7 (2203)	94.6 (2403)
h3 - Mast lifting height	in (mm)	115.6 (2936)	135.3 (3436)	151 (3836)
h4 - Mast extended height	in (mm)	133.5 (3390)	153.1 (3890)	168.9 (4290)
Residual capacity at max height	lb (kg)	2646 (1200)	2315 (1050)	1764 (800)

Free Lift Duplex (FLD)		FLD 29	FLD 34
h1 - Mast lowered height	in (mm)	76.9 (1953)	86.7 (2203)
h2 - Mast free lift	in (mm)	59.3 (1506)	69.1 (1756)
h3 - Mast lifting height	in (mm)	115.4 (2931)	135.1 (3431)
h4 - Mast extended height	in (mm)	133267.7 (3385000)	153 (3885)
Residual capacity at max height	lb (kg)	2646 (1200)	2315 (1050)

Free Lift Triplex (FLT)		FLT 42	FLT 45
h1 - Mast lowered height	in (mm)	75.2 (1911)	81.5 (2071)
h2 - Mast free lift	in (mm)	57.7 (1466)	64 (1626)
h3 - Mast lifting height	in (mm)	167.2 (4246)	186.1 (4726)
h4 - Mast extended height	in (mm)	185.9 (4723)	204.8 (5203)
Residual capacity at max height	lb (kg)	1433 (650)	1279 (580)



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes