
Technical sheet :


KLEOS HM 250 D18



MANITOU
HANDLING YOUR WORLD

	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		HM 250 D18	HM 250 D18
1.3	Power source		Manual	Manual
1.4	Operator type		Pedestrian	Pedestrian
1.5	Max. capacity	Q	250 kg	551 lb
1.6	Load center of gravity	c	250 mm	10 in
	Weight			
2.1	Overall weight without tools		110 kg	243 lb
	Wheels			
3.1	Tires type		Nylon	Nylon
3.2	Dimensions of front wheels		2x (75x65)	2x (75x65)
3.3	Dimensions of rear wheels		2x (150x50)	2x (150x50)
	Dimensions			
4.2	Mast lowered height	h1	1585 mm	62 in
4.5	Mast extended height	h4	2475 mm	97 in
4.19	Overall length	l1	1032 mm	41 in
4.20	Length to face of forks	l2	571 mm	22 in
4.21	Overall width	b1	710 mm	28 in
4.25	Fork spread	b5	529 mm	21 in
	Performances			
5.2	Lifting speed (laden / unladen)		0.10 m/s / 0.10 m/s	0.33 ft/s / 0.33 ft/s
5.3	Lowering speed (laden / unladen)		0.10 m/s / 0.10 m/s	0.33 ft/s / 0.33 ft/s
5.11	Parking brake		Mecanic	Mecanic

Kleos HM 250 D18 - Dimensional drawing




Tool characteristics


Tool 250 kg	Attachment capacity	Center of gravity of load	A1	A2	B	B1		C	D	E	E1	E2	F	Weight
	lb (kg)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	lb (kg)
EPE 250	551 (250)	9.8 (250)	19.7 (500)	20.3 (515)	1.6 (40)	-	-	10.6 (270)	-	-	-	-	12.6 (320)	46 (21)
FA 250	551 (250)	9.8 (250)	19.7 (500)	21.3 (540)	-	9.1 (230)	25.6 (650)	2 (50)	2 (50)	0.80 (20)	-	-	26.8 (680)	73 (33)
PLF 250	441 (200)	11.8 (300)	24.4 (620)	25 (635)	19.7 (500)	-	-	11 (280)	-	3.5 (88)	-	-	24.8 (630)	88 (40)
POT 250	331 (150)	15.7 (400)	16.7 (425)	17.3 (440)	2 (50)	-	-	6.7 (170)	-	-	-	-	12.6 (320)	48 (22)

Tools


EPE 250




FA 250



PLF 250



POT 250



Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes