

Technical sheet :

ME 435



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics			Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		ME 435	ME 435
1.3	Power source		Electrical	Electrical
1.4	Operator type		Seated	Seated
1.5	Max. capacity	Q	3500 kg	7716 lb
1.6	Load center of gravity	c	500 mm	20 in
1.8	Load distance, centre of drive axle to fork	x	445 mm	18 in
1.9	Wheelbase	y	1750 mm	69 in
Weight				
	Standard mast reference of the machine		FLT 60	FLT 60
2.1	Service weight		5550 kg	12236 lb
2.2	Weight on front axle (laden) / rear axle (laden)		8050 kg / 1000 kg	17747 lb / 2205 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		2720 kg / 2830 kg	5997 lb / 6239 lb
Wheels				
3.1	Tires type		Solid tires	Solid tires
3.2	Dimensions of front wheels		23 x 10 -12	23 x 10 -12
3.3	Dimensions of rear wheels		200/50 - 10	200/50 - 10
3.5	Number of front wheels / rear wheels		2 / 2	2 / 2
3.5.2	Number of drive wheels		2	2
3.6	Front wheel gauge	b10	1085 mm	43 in
3.7	Rear wheel gauge	b11	960 mm	38 in
Dimensions				
4.7	Height of overhead guard (cabin)	h6	2240 mm	88 in
4.8	Seat height/stand height	h7	1190 mm	47 in
4.12	Height of towing bar (coupling height)	h10	625 mm	25 in
4.19	Overall length	l1	3650 mm	144 in
4.20	Length to face of forks	l2	2500 mm	98 in
4.21	Overall width	b1	1315 mm	52 in
4.22	Forks section / width / length	s / e / l	50 mm x 122 mm x 1150 mm	2 in x 5 in x 45 in
4.23	Fork carriage ISO 2328 (class/form) A/B		3A	3A
4.24	Fork carriage width	b3	1100 mm	43 in
4.31	Ground clearance below mast	m1	112 mm	4 in
4.32	Ground clearance at centre of wheelbase	m2	115 mm	5 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	4045 mm	159 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	4245 mm	167 in
4.35	Turning radius	Wa	2400 mm	94 in
4.36	Internal turning radius (over tyres)	b13	730 mm	29 in
Performances				
5.1	Travel speed (laden / unladen)		19 km/h-20 km/h	12 mph-12 mph
5.2	Lifting speed (laden / unladen)		0.39 m/s-0.54 m/s	1 ft/s-2 ft/s
5.3	Lowering speed (laden / unladen)		0.47 m/s-0.42 m/s	2 ft/s-1 ft/s
5.5	Drawbar pull (Laden / Unladen)		1690 daN / 1700 daN	1690 daN / 1700 daN
5.7	Gradeability (laden / unladen)		12 % / 18 %	12 % / 18 %
5.10	Service brake		Oil bath	Oil bath
Engine				
6.1	Drive motor rating S2 60 min		18.50 kW	18.50 kW
6.2	Lift motor rating at S3 15%		25.40 kW	25.40 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN43536 A	DIN43536 A
6.4	Battery voltage / capacity		80 V / 700 Ah	80 V / 700 Ah
6.6	Energy consumption according to VDI cycle (kW/h)		12.50 kWh	12.50 kWh
Miscellaneous				
8.1	Type of drive control		Electronic	Electronic
8.2	Working hydraulic pressure for attachments		210 bar	3046 PSI
8.3	Oil flow rate for attachments		65 l/min	17 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 74 dB	< 74 dB

ME 435 - Dimensional drawing





Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes