

Technical sheet :


ME 320



 **MANITOU**
HANDLING YOUR WORLD

Technical characteristics			Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		ME 320	ME 320
1.3	Power source		Electrical	Electrical
1.4	Operator type		Seated	Seated
1.5	Max. capacity	Q	2000 kg	4409 lb
1.6	Load center of gravity	c	500 mm	20 in
1.8	Load distance, centre of drive axle to fork	x	355 mm	14 in
1.9	Wheelbase	y	1465 mm	58 in
Weight				
2.1	Service weight		3470 kg	7650 lb
2.2	Weight on front axle (laden) / rear axle (laden)		4750 kg / 720 kg	10472 lb / 1587 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1530 kg / 1940 kg	3373 lb / 4277 lb
Wheels				
3.1	Tires type		Solid tires	Solid tires
3.2	Dimensions of front wheels		200/50-10	200/50-10
3.3	Dimensions of rear wheels		15x4,5-8	15x4,5-8
3.5	Number of front wheels / rear wheels		2 / 1	2 / 1
3.5.2	Number of drive wheels		2	2
3.6	Front wheel gauge	b10	910 mm	36 in
3.7	Rear wheel gauge	b11	175 mm	7 in
Dimensions				
4.7	Height of overhead guard (cabin)	h6	2040 mm	80 in
4.8	Seat height/stand height	h7	1000 mm	39 in
4.12	Height of towing bar (coupling height)	h10	500 mm	20 in
4.19	Overall length	l1	3076 mm	121 in
4.20	Length to face of forks	l2	2006 mm	79 in
4.21	Overall width	b1	1120 mm	44 in
4.22	Forks section / width / length	s / e / l	40 mm x 122 mm x 1070 mm	2 in x 5 in x 42 in
4.23	Fork carriage ISO 2328 (class/form) A/B		2A	2A
4.24	Fork carriage width	b3	1000 mm	39 in
4.31	Ground clearance below mast	m1	100 mm	4 in
4.32	Ground clearance at centre of wheelbase	m2	110 mm	4 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	3346 mm	132 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	3470 mm	137 in
4.35	Turning radius	Wa	1660 mm	65 in
Performances				
5.1	Travel speed (laden / unladen)		15 km/h-15 km/h	9 mph-9 mph
5.2	Lifting speed (laden / unladen)		0.40 m/s-0.45 m/s	1 ft/s-1 ft/s
5.3	Lowering speed (laden / unladen)		0.47 m/s-0.42 m/s	2 ft/s-1 ft/s
5.5	Drawbar pull (Laden / Unladen)		900 daN / 930 daN	900 daN / 930 daN
5.7	Gradeability (laden / unladen)		13 % / 15 %	13 % / 15 %
5.10	Service brake		Oil bath	Oil bath
Engine				
6.1	Number of drive motor / Drive motor rating S2 60 min		2 / 4.50 kW	2 / 4.50 kW
6.2	Lift motor rating at S3 15%		8.60 kW	8.60 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN43531 A	DIN43531 A
6.4	Battery voltage / capacity		48 V / 690 Ah	48 V / 690 Ah
6.6	Energy consumption according to VDI cycle (kWh/h)		4.70 kWh/h	4.70 kWh/h
Miscellaneous				
8.1	Type of drive control		Electronic	Electronic
8.2	Working hydraulic pressure for attachments		180 bar	2611 PSI
8.3	Oil flow rate for attachments		35 l/min	9 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 70 dB	< 70 dB
8.4	Sound level at the driver's ear according to DIN 12 053		70 dB	70 dB

ME 320 - Dimensional drawing



Full Visibility Duplex (FVD)		FVD 27	FVD 30	FVD 33	FVD 36	FVD 40	FVD 43	FVD 45
α - Mast/fork carriage tilt, forward °		5.50	5.50	5.50	5.50	3.50	3.50	3.50
β - Mast/fork carriage tilt, backward °		6	6	6	6	5	5	5
h1 - Mast lowered height	in (mm)	72.6 (1845)	78.5 (1995)	84.4 (2145)	90.4 (2295)	100.2 (2545)	106.7 (2710)	111 (2820)
h2 - Mast free lift	in (mm)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)	5.7 (145)
h3 - Mast lifting height	in (mm)	106.3 (2700)	118.1 (3000)	129.9 (3300)	141.7 (3600)	157.5 (4000)	169.3 (4300)	177.2 (4500)
h4 - Mast extended height	in (mm)	128.5 (3265)	140.4 (3565)	152.2 (3865)	164 (4165)	179.7 (4565)	191.5 (4865)	199.4 (5065)
Residual capacity at max height	lb (kg)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4299 (1950)	4189 (1900)
Residual capacity with integrated side shift at max height	lb (kg)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4299 (1950)	4189 (1900)
Residual capacity with hooked-on side shift at max height	lb (kg)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4079 (1850)	3858 (1750)	3748 (1700)
Height at max capacity	in (mm)	106.3 (2700)	118.1 (3000)	129.9 (3300)	141.7 (3600)	157.5 (4000)	157.5 (4000)	157.5 (4000)
Height at max capacity with integrated side shift	in (mm)	106.3 (2700)	118.1 (3000)	129.9 (3300)	141.7 (3600)	157.5 (4000)	157.5 (4000)	157.5 (4000)

Free Lift Duplex (FLD)		FLD 27	FLD 30	FLD 33	FLD 36	FLD 40
α - Mast/fork carriage tilt, forward	°	5.50	5.50	5.50	5.50	3.50
β - Mast/fork carriage tilt, backward	°	6	6	6	6	5
h1 - Mast lowered height	in (mm)	72.6 (1845)	78.5 (1995)	84.4 (2145)	90.4 (2295)	100.2 (2545)
h2 - Mast free lift	in (mm)	49.6 (1260)	55.5 (1410)	61.4 (1560)	67.3 (1710)	77.2 (1960)
h3 - Mast lifting height	in (mm)	106.3 (2700)	118.1 (3000)	129.9 (3300)	141.7 (3600)	157.5 (4000)
h4 - Mast extended height	in (mm)	129.7 (3295)	141.5 (3595)	153.3 (3895)	165.2 (4195)	180.9 (4595)
Residual capacity at max height	lb (kg)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)
Residual capacity with integrated side shift at max height	lb (kg)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)
Residual capacity with hooked-on side shift at max height	lb (kg)	4409 (2000)	4409 (2000)	4409 (2000)	4409 (2000)	4079 (1850)
Height at max capacity	in (mm)	106.3 (2700)	118.1 (3000)	129.9 (3300)	141.7 (3600)	157.5 (4000)
Height at max capacity with integrated sideshift	in (mm)	106.3 (2700)	118.1 (3000)	129.9 (3300)	141.7 (3600)	157.5 (4000)

[illegible]



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes