



Technical sheet :

# CT 40



	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		CT 40	CT 40
1.3	Power source		Electrical	Electrical
1.4	Operator type		Carried	Carried
1.5	Max. capacity	Q	4000 kg	8818 lb
1.9	Wheelbase	y	1109 mm	44 in
	<b>Weight</b>			
2.1	Service weight		1270 kg	2800 lb
2.3	Axle loading unladen (front / rear)		800 kg / 470 kg	1764 lb / 1036 lb
	<b>Wheels</b>			
3.1	Tires type		Bandage	Bandage
3.2	Dimensions of front wheels		254 x 100	254 x 100
3.3	Dimensions of rear wheels		250 x 75	250 x 75
3.4	Additional wheels (dimensions)		140 x 40	140 x 40
3.5	Number of front wheels / rear wheels		2 / 2	2 / 2
3.5.2	Number of drive wheels		1	1
3.5.2	Drive wheels (front / rear)		1 / 0	1 / 0
3.6	Front wheel gauge	b10	581 mm	23 in
3.7	Rear wheel gauge	b11	633 mm	25 in
	<b>Dimensions</b>			
4.9	Height tiller up max.*	h14	1212 mm	48 in
4.12	Height of towing bar (coupling height)	h10	220 mm	9 in
4.17	Coupling distance to rear axle	l5	255 mm	10 in
4.19	Overall length	l1	1551 mm	61 in
4.21	Overall width	b1	800 mm	31 in
4.32	Ground clearance at centre of wheelbase	m2	50 mm	2 in
4.35	Turning radius	Wa	1332 mm	52 in
	<b>Performances</b>			
5.1	Travel speed (laden / unladen)		8 km/h / 12 km/h	5 mph / 7 mph
5.8	Max Gradeability (laden / unladen)		4 % / 13 %	4 % / 13 %
5.10	Service brake		Electro magnetic	Electro magnetic
5.11	Parking brake		Butterfly switch release	Butterfly switch release
	<b>Engine</b>			
6.1	Drive motor rating S2 60 min		2 kW	2 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		Traction	Traction
6.4	Battery voltage / capacity		24 V / 465 Ah	24 V / 465 Ah
6.5	Battery weight (+/- 5%)		460 kg	1014 lb
	<b>Miscellaneous</b>			
8.1	Type of drive control		Mosfet AC speed controller	Mosfet AC speed controller
8.4	Sound level at the driver's ear according to DIN 12 053		66 dB	66 dB

## CT 40 - Dimensional drawing



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes