

Technical sheet :


MI 45 D



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Metric	Imperial
1.1	Manufacturer		Manitou	Manitou
1.2	Model Name		MI 45 D	MI 45 D
1.3	Power source		Diesel	Diesel
1.4	Operator type		Seated	Seated
1.5	Max. capacity	Q	4500 kg	9921 lb
1.6	Load center of gravity	c	500 mm	20 in
1.8	Load distance, centre of drive axle to fork	x	550 mm	22 in
1.9	Wheelbase	y	2000 mm	79 in
	Standard mast reference of the machine		FVD 30	FVD 30
	Weight			
2.1	Service weight		6500 kg	14330 lb
2.2	Weight on front axle (laden) / rear axle (laden)		9625 kg / 1375 kg	21219 lb / 3031 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		2820 kg / 3680 kg	6217 lb / 8113 lb
	Wheels			
3.1	Tires type		Pneumatic	Pneumatic
3.2	Dimensions of front wheels		300-15-18PR	300-15-18PR
3.3	Dimensions of rear wheels		7.00-12-12PR	7.00-12-12PR
3.5	Number of front wheels / rear wheels		2 / 2	2 / 2
3.5.2	Number of drive wheels		2	2
3.6	Front wheel gauge	b10	1190 mm	47 in
3.7	Rear wheel gauge	b11	1130 mm	44 in
	Dimensions			
4.7	Height of overhead guard (cabin)	h6	2390 mm	94 in
4.8	Seat height/stand height	h7	1370 mm	54 in
4.12	Height of towing bar (coupling height)	h10	445 mm	18 in
4.19	Overall length	l1	4330 mm	170 in
4.20	Length to face of forks	l2	3110 mm	122 in
4.21	Overall width	b1	1490 mm	59 in
4.21	Overall width - Single wheels	b1	1490 mm	59 in
4.22	Forks section / width / length	s / e / l	50 mm x 150 mm x 1220 mm	2 in x 6 in x 48 in
4.23	Fork carriage ISO 2328 (class/form) A/B		3A	3A
4.24	Fork carriage width	b3	1250 mm	49 in
4.31	Ground clearance below mast	m1	170 mm	7 in
4.32	Ground clearance at centre of wheelbase	m2	230 mm	9 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	4662 mm	184 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	4795 mm	189 in
4.35	Turning radius	Wa	2800 mm	110 in
4.36	Internal turning radius (over tyres)	b13	100 mm	4 in
	Performances			
5.1	Travel speed (laden / unladen)		22 km/h-24 km/h	14 mph-15 mph
5.2	Lifting speed (laden / unladen)		0.46 m/s-0.48 m/s	2 ft/s-2 ft/s
5.3	Lowering speed (laden / unladen)		0.50 m/s-0.50 m/s	2 ft/s-2 ft/s
5.5	Drawbar pull (Laden / Unladen)		4000 daN / 2000 daN	4000 daN / 2000 daN
5.7	Gradeability (laden / unladen)		30 % / 36 %	30 % / 36 %
5.10	Service brake		Hydraulic	Hydraulic
	Transmission type		Torque converter	Torque converter
	Engine			
7.1	Engine brand / model		Cummins / QSF2.8T4F	Cummins / QSF2.8T4F
7.2	I.C. Engine power rating		55 kW	55 kW
7.3	Rated speed		2600 rpm	2600 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 2800 cm³	4 - 171 in³
	Miscellaneous			
8.2	Working hydraulic pressure for attachments		160 bar	2321 PSI
8.3	Oil flow rate for attachments		90 l/min	24 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 84 dB	< 84 dB
8.4	Sound level at the driver's ear according to DIN 12 053		84 dB	84 dB

MI 45 D - Dimensional drawing



[illegible]



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes