

Technical sheet :

# MI-X 45 D


---



 **MANITOU**  
HANDLING YOUR WORLD

| Technical characteristics |                                                                 |           | Metric                   | Imperial            |
|---------------------------|-----------------------------------------------------------------|-----------|--------------------------|---------------------|
| 1.1                       | Manufacturer                                                    |           | Manitou                  | Manitou             |
| 1.2                       | Model Name                                                      |           | MI-X 45 D                | MI-X 45 D           |
| 1.3                       | Power source                                                    |           | Diesel                   | Diesel              |
| 1.4                       | Operator type                                                   |           | Seated                   | Seated              |
| 1.5                       | Max. capacity                                                   | Q         | 4500 kg                  | 9921 lb             |
| 1.6                       | Load center of gravity                                          | c         | 500 mm                   | 20 in               |
| 1.8                       | Load distance, centre of drive axle to fork                     | x         | 550 mm                   | 22 in               |
| 1.9                       | Wheelbase                                                       | y         | 2000 mm                  | 79 in               |
| Weight                    |                                                                 |           |                          |                     |
| 2.1                       | Service weight                                                  |           | 6500 kg                  | 14330 lb            |
| 2.2                       | Weight on front axle (laden) / rear axle (laden)                |           | 9625 kg / 1375 kg        | 21219 lb / 3031 lb  |
| 2.3                       | Weight on front axle (Unladen) / rear axle (Unladen)            |           | 2820 kg / 3680 kg        | 6217 lb / 8113 lb   |
| Wheels                    |                                                                 |           |                          |                     |
| 3.1                       | Tires type                                                      |           | Pneumatic                | Pneumatic           |
| 3.2                       | Dimensions of front wheels                                      |           | 300-15-18PR              | 300-15-18PR         |
| 3.3                       | Dimensions of rear wheels                                       |           | 7.00-12-12PR             | 7.00-12-12PR        |
| 3.5                       | Number of front wheels / rear wheels                            |           | 2 / 2                    | 2 / 2               |
| 3.5.2                     | Number of drive wheels                                          |           | 2                        | 2                   |
| 3.6                       | Front wheel gauge                                               | b10       | 1190 mm                  | 47 in               |
| 3.7                       | Rear wheel gauge                                                | b11       | 1130 mm                  | 44 in               |
| Dimensions                |                                                                 |           |                          |                     |
| 4.7                       | Height of overhead guard (cabin)                                | h6        | 2390 mm                  | 94 in               |
| 4.8                       | Seat height/stand height                                        | h7        | 1370 mm                  | 54 in               |
| 4.12                      | Height of towing bar (coupling height)                          | h10       | 445 mm                   | 18 in               |
| 4.19                      | Overall length                                                  | l1        | 4330 mm                  | 170 in              |
| 4.20                      | Length to face of forks                                         | l2        | 3110 mm                  | 122 in              |
| 4.21                      | Overall width                                                   | b1        | 1490 mm                  | 59 in               |
| 4.21                      | Overall width - Single wheels                                   | b1        | 1490 mm                  | 59 in               |
| 4.21                      | Overall width - Twinned wheels                                  | b1        | 1940 mm                  | 76 in               |
| 4.22                      | Forks section / width / length                                  | s / e / l | 50 mm x 150 mm x 1220 mm | 2 in x 6 in x 48 in |
| 4.23                      | Fork carriage ISO 2328 (class/form) A/B                         |           | 3A                       | 3A                  |
| 4.24                      | Fork carriage width                                             | b3        | 1250 mm                  | 49 in               |
| 4.31                      | Ground clearance below mast                                     | m1        | 170 mm                   | 7 in                |
| 4.32                      | Ground clearance at centre of wheelbase                         | m2        | 230 mm                   | 9 in                |
| 4.33                      | Aisle Width for pallets 1000 x 1200 crossways                   | Ast       | 4662 mm                  | 184 in              |
| 4.34                      | Aisle width for 800 x 1200 pallet lengthways                    | Ast       | 4795 mm                  | 189 in              |
| 4.35                      | Turning radius                                                  | Wa        | 2800 mm                  | 110 in              |
| 4.36                      | Internal turning radius (over tyres)                            | b13       | 100 mm                   | 4 in                |
| Performances              |                                                                 |           |                          |                     |
| 5.1                       | Travel speed (laden / unladen)                                  |           | 22 km/h-24 km/h          | 14 mph-15 mph       |
| 5.2                       | Lifting speed (laden / unladen)                                 |           | 0.46 m/s-0.48 m/s        | 2 ft/s-2 ft/s       |
| 5.3                       | Lowering speed (laden / unladen)                                |           | 0.50 m/s-0.50 m/s        | 2 ft/s-2 ft/s       |
| 5.5                       | Drawbar pull (Laden / Unladen)                                  |           | 3800 daN / 2200 daN      | 3800 daN / 2200 daN |
| 5.7                       | Gradeability (laden / unladen)                                  |           | 34 % / 34 %              | 34 % / 34 %         |
| 5.10                      | Service brake                                                   |           | Hydraulic                | Hydraulic           |
| Engine                    |                                                                 |           |                          |                     |
| 7.1                       | Engine brand / model                                            |           | Perkins / 1104D-44       | Perkins / 1104D-44  |
| 7.2                       | Engine power according to ISO 1585                              |           | 56 kW                    | 56 kW               |
| 7.3                       | Rated speed                                                     |           | 2200 rpm                 | 2200 rpm            |
| 7.4                       | Number of cylinders / Capacity of cylinders                     |           | 4 - 4400 cm³             | 4 - 269 in³         |
| Miscellaneous             |                                                                 |           |                          |                     |
| 8.2                       | Working hydraulic pressure for attachments                      |           | 160 bar                  | 2321 PSI            |
| 8.3                       | Oil flow rate for attachments                                   |           | 90 l/min                 | 24 US gpm           |
| 8.4                       | Measured/guaranteed mean noise level at the ear of the operator |           | < 87 dB                  | < 87 dB             |
| 8.4                       | Sound level at the driver's ear according to DIN 12 053         |           | 87 dB                    | 87 dB               |

## MI-X 45 D - Dimensional drawing



| Full Visibility Duplex (FVD)                               |         | FVD 30       | FVD 33       | FVD 35       | FVD 37       | FVD 40       | FVD 45       | FVD 50       |
|------------------------------------------------------------|---------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Mast/fork carriage tilt, forward                           | °       | 6            | 6            | 6            | 6            | 6            | 6            | 6            |
| Mast/fork carriage tilt, backward                          | °       | 12           | 12           | 12           | 12           | 12           | 6            | 6            |
| h1 - Mast lowered height                                   | in (mm) | 88.4 (2245)  | 94.3 (2395)  | 98.2 (2495)  | 102.2 (2595) | 110 (2795)   | 120.9 (3070) | 131.7 (3345) |
| h2 - Mast free lift                                        | in (mm) | 6.3 (160)    | 6.3 (160)    | 6.3 (160)    | 6.3 (160)    | 6.3 (160)    | 6.3 (160)    | 6.3 (160)    |
| h3 - Mast lifting height                                   | in (mm) | 118.1 (3000) | 129.9 (3300) | 137.8 (3500) | 145.7 (3700) | 157.5 (4000) | 177.2 (4500) | 196.9 (5000) |
| h4 - Mast extended height                                  | in (mm) | 164.2 (4170) | 176 (4470)   | 183.9 (4670) | 191.7 (4870) | 203.5 (5170) | 223.2 (5670) | 242.9 (6170) |
| Residual capacity at max height                            | lb (kg) | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 9039 (4100)  | 8157 (3700)  |
| Residual capacity with integrated side shift at max height | lb (kg) | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 8818 (4000)  | 7937 (3600)  |
| Height at max capacity                                     | in (mm) | 118.1 (3000) | 129.9 (3300) | 137.8 (3500) | 145.7 (3700) | 157.5 (4000) | 157.5 (4000) | 157.5 (4000) |
| Height at max capacity with integrated sideshift           | in (mm) | 118.1 (3000) | 129.9 (3300) | 137.8 (3500) | 145.7 (3700) | 157.5 (4000) | 157.5 (4000) | 157.5 (4000) |

| Free Lift Duplex (FLD)                                     |         | FLD 30       | FLD 33       | FLD 35       | FLD 37       |
|------------------------------------------------------------|---------|--------------|--------------|--------------|--------------|
| Mast/fork carriage tilt, forward                           | °       | 6            | 6            | 6            | 6            |
| Mast/fork carriage tilt, backward                          | °       | 12           | 12           | 12           | 12           |
| h1 - Mast lowered height                                   | in (mm) | 87.6 (2226)  | 93.5 (2376)  | 97.5 (2476)  | 101.4 (2576) |
| h2 - Mast free lift                                        | in (mm) | 53.7 (1364)  | 59.6 (1514)  | 63.5 (1614)  | 67.5 (1714)  |
| h3 - Mast lifting height                                   | in (mm) | 118.1 (3000) | 129.9 (3300) | 137.8 (3500) | 145.7 (3700) |
| h4 - Mast extended height                                  | in (mm) | 164.2 (4170) | 176 (4470)   | 183.9 (4670) | 191.7 (4870) |
| Residual capacity at max height                            | lb (kg) | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  |
| Residual capacity with integrated side shift at max height | lb (kg) | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  | 9921 (4500)  |
| Height at max capacity                                     | in (mm) | 118.1 (3000) | 129.9 (3300) | 137.8 (3500) | 145.7 (3700) |
| Height at max capacity with integrated sideshift           | in (mm) | 118.1 (3000) | 129.9 (3300) | 137.8 (3500) | 145.7 (3700) |

[illegible]



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes