

Technical sheet :

# 2200R


---



 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Metric	Imperial
Rated Operating Capacity		998 kg	2200 lb
Rated Operating Capacity with Optional Counterweight		1075 kg	2370 lb
Unladen weight		3620 kg	7981 lb
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	4089 mm	161 in
Height to Hinge Pin – Fully Raised	h28	3124 mm	123 in
Overall Height to top of ROPS	h17	2057 mm	81 in
Dump angle at full height	a5	40 °	40 °
Dump height	h29	2388 mm	94 in
Overall length with bucket	l16	3467 mm	136 in
Dump reach - Full height	r6	686 mm	27 in
Rollback at ground	a13	28 °	28 °
Seat to ground height	h30	1016 mm	40 in
Wheelbase	y	1092 mm	43 in
Overall width less bucket	b1	1664 mm	66 in
Bucket Width	e1	1778 mm	70 in
Ground clearance	m4	203 mm	8 in
Overall length - Less Bucket	l2	2667 mm	105 in
Departure angle	a2	25 °	25 °
Clearance Circle - Front without Bucket	b19	1321 mm	52 in
Clearance Circle - Rear	wa1	1524 mm	60 in
Performances			
Travel Speed with Two-Speed Option - Maximum		19.20 km/h	12 mph
Travel speed (unladen)		12.90 km/h	8 mph
Wheels			
Standard tires		12.00x16.5 HD	12.00x16.5 HD
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV88CT-NMS	4TNV88CT-NMS
Engine norm		Stage V	Stage V
Gross Power		53.70 kW	53.70 kW
Net Power		52.70 kW	52.70 kW
Max. torque / Engine rotation		294 Nm / 2500 rpm	217 ft/lbs / 2500 rpm
I.C. Engine power rating		72 Hp	72 Hp
Battery voltage		12 V	12 V
Alternator		95 kW	95 kW
Starter		3 kW	3 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		90 l/min	24 US gpm
Auxiliary Hydraulic Pressure		227.50 bar	3300 PSI
High-Flow Auxiliary Hydraulics – Option		132.50 l/min	35 US gpm
High-Flow Auxiliary Hydraulics Pressure – Option		220.60 bar	3200 PSI
Tank capacities			
Fuel tank		68.10 l	18 US gal
Reservoir Capacity Hydraulics		30.30 l	8 US gal
Displacement		3.30 l	0.87 US gal
Noise and vibration			
Environmental noise (LwA)		101 dB	101 dB
Noise at driving position (LpA)		85 dB	85 dB
Whole-Body Vibration (ISO 2631-1)		0.96 m/s²	0.96 m/s²
Vibration to whole hand/arm		< 1.50 m/s²	< 1.50 m/s²

2200R - Dimensional drawing



## Equipment

—	
Integral Access Plate (removable)	Standard
<b>Lifting function</b>	
All-Tach® Attachment Mounting System	Standard
Auxiliary Hydraulics	Standard
Power-A-Tach® Attachment Mounting System	Optional
<b>Lighting</b>	
Work Lights - Front and Rear	Standard
<b>Motorization/Power</b>	
Engine Auto-Shutdown System	Standard
Engine Block Heater	Optional
Turbo-Charged Engine	Standard
Two-Speed Drive	Optional
<b>Operator station</b>	
Adjustable Arm Rests / Control Towers 1	Standard
Air conditioning with manual adjustment	Optional
Air suspension seat	Optional
Cab Enclosure	Optional
Dual-Hand Controls	Optional
Foot and Hand Throttles 2	Standard
Gehl T-Bar Controls	Optional
Hand/Foot Controls	Optional
Heating	Optional
High-Back Adjustable Seat	Standard
Horn	Standard
Joystick controls	Optional
ROPS/FOPS Level II Overhead Guard	Standard
Sound Reduction Material	Standard
Suspension Seat - Mechanical	Optional
<b>Other options</b>	
Hydrostatic Drive - Servo	Standard
Selectable Self-Leveling Hydraulic Lift Action 4	Optional
<b>Secondary functions</b>	
Counterweight	Optional
Full Instrumentation	Standard
Hydraglide™ Ride Control 3	Optional
<b>Security</b>	
Anti-Vandalism Protection	Standard
Back-Up Alarm	Optional
Brake Control (Auto / Manual)	Standard
Hydraloc™ Safety System	Standard
Lift Arm Support Device	Standard
Operator Restraint Bar	Standard



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes