

Technical sheet :

# MLA 1-25 H

---



 **MANITOU**  
HANDLING YOUR WORLD


Capacities		Metric	Imperial
Static tipping load with bucket (straight)		875 kg	1929 lb
Static tipping load with bucket (full turn)		702 kg	1548 lb
Static tipping load with forks (straight)		666 kg	1468 lb
Static tipping load with forks (full turn)		523 kg	1153 lb
Max. height of bucket pivot point	h35	2.71 m	8 ft 11 in
Max. lifting height (below forks)	h3	2.50 m	8 ft 2 in
Breakout force with bucket		1080 daN	1080 daN
Weight and dimensions			
Unladen weight (with forks) with 4-post canopy		1744 kg	3845 lb
Wheelbase	y	1.35 m	4 ft 5 in
Overall width of 4 posts canopy	b22	0.79 m	2 ft 7 in
Overall height with 4 posts canopy	h38	2.19 m	7 ft 2 in
Tilt-up angle	a4	40 °	40 °
Tilt-down angle	a5	45 °	45 °
Articulation angle	a19	45 °	45 °
Overall width less bucket	b1	0.86 m	2 ft 10 in
Overall length - Less Bucket	l2	2.74 m	9 ft
Standard tires		Mitas - As Farmer - 7 00 12	Mitas - As Farmer - 7 00 12
Ground clearance	m4	0.19 m	7 in
Engine			
Engine brand		Yanmar	Yanmar
Engine model		3TNV76	3TNV76
Engine nom		Stage IIIA	Stage IIIA
Number of cylinders / Capacity of cylinders		3 - 1100 cm³	3 - 67 in³
I.C. Engine power rating / Power		24.33 Hp / 18 kW	24.33 Hp / 18 kW
Max. torque / Engine rotation		65.60 Nm / 1800 rpm	48 ft/lbs / 1800 rpm
Engine cooling system		2 radiators water + hydraulic oil	2 radiators water + hydraulic oil
Transmission			
Transmission type		Hydrostatic	Hydrostatic
Number of gears (forward / reverse)		1 / 1	1 / 1
Max. travel speed (may vary according to applicable regulations)		13 km/h	8 mph
Differential lock		Limited slip differential on front and rear axles	Limited slip differential on front and rear axles
Parking brake		Manual	Manual
Hydraulics			
Hydraulic pump type		Gear pump	Gear pump
Hydraulic flow - Pressure		30 l/min / 207 bar	8 US gpm / 3002 PSI
Drive hydraulic system pressure		320 bar	4641 PSI
Tank capacities			
Hydraulic oil		34 l	9 US gal
Fuel tank		26 l	7 US gal
Noise and vibration			
Vibration on hands/arms		< 2.50 m/s²	< 2.50 m/s²
Miscellaneous			
Cab certification		ROPS - FOPS cab (level 1)	ROPS - FOPS cab (level 1)

## Options / Finishing

S : Standard / O : Optional / - : Not available

	Essential
Lifting function	
Attachment hydraulic line	S
Hydraulic attachment locking	O
Operator station	
Adjustable and telescopic steering column	O
Canopy	S
Motorization/Power	
Continuous flow hydraulics	S
Self cleaning air prefilter	S
Lighting	
Complete road lighting	O

MLA 1-25 H - Dimensional drawing





**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes