

Technical sheet :

# 3300V NXT2

---



 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Metric	Imperial
Rated Operating Capacity		1497 kg	3300 lb
Unladen weight		4123 kg	9090 lb
Weight and dimensions			
Wheelbase	y	1257 mm	49 in
Overall Operating Height - Fully Raised	h27	4369 mm	172 in
Height to Hinge Pin - Fully Raised	h28	3332 mm	131 in
Overall Height to top of ROPS	h17	2083 mm	82 in
Dump angle at full height	a5	42 °	42 °
Dump height	h29	2502 mm	99 in
Overall length with bucket	l16	3874 mm	153 in
Dump reach - Full height	r6	813 mm	32 in
Rollback at ground	a13	29 °	29 °
Seat to ground height	h30	1041 mm	41 in
Overall width less bucket	b1	1829 mm	72 in
Bucket Width	e1	1880 mm	74 in
Ground clearance	m4	229 mm	9 in
Overall length - Less Bucket	l2	3023 mm	119 in
Departure angle	a2	25 °	25 °
Clearance Radius - Front with Bucket	b18	2400 mm	94 in
Performances			
Travel speed (unladen)		13 km/h	8 mph
Travel Speed with Two-Speed Option - Maximum		19.60 km/h	12 mph
Wheels			
Standard tires		14.00 x 17.5 HD	14.00 x 17.5 HD
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV98CT-NMS	4TNV98CT-NMS
Engine norm		Stage V	Stage V
Gross Power		53.70 kW	53.70 kW
Net Power		52.70 kW	52.70 kW
Max. torque / Engine rotation		294 Nm / 2500 rpm	217 ft/lbs / 2500 rpm
Power source		Diesel	Diesel
I.C. Engine power rating		72 Hp	72 Hp
Battery voltage		12 V	12 V
Alternator		95 kW	95 kW
Starter		3 kW	3 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		89.10 l/min	24 US gpm
Auxiliary Hydraulic Pressure		237.90 bar	3450 PSI
High-Flow Auxiliary Hydraulics - Option		132 l/min	35 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		220.60 bar	3200 PSI
Tank capacities			
Fuel tank		92.70 l	24 US gal
Hydraulic tank capacity		40 l	11 US gal
Displacement		3.30 l	0.87 US gal
Noise and vibration			
Noise to environment (LwA)		101 dB	101 dB
Noise at driving position (LpA)		85 dB	85 dB
Whole-Body Vibration (ISO 2631-1)		0.79 m/s²	0.79 m/s²
Vibration on hands/arms		< 1.20 m/s²	< 1.20 m/s²

3300V NXT2 - Dimensional drawing



## Equipment

—	
Integral Access Plate (removable)	Standard
<b>Lifting function</b>	
All-Tach® Attachment Mounting System	Standard
Auxiliary Hydraulics	Standard
High-Flow Auxiliary Hydraulics	Optional
Power-A-Tach® Attachment Mounting System	Optional
<b>Lighting</b>	
Work Lights - Front and Rear	Standard
<b>Motorization/Power</b>	
Engine Auto-Shutdown System	Standard
Engine Block Heater	Optional
Turbo-Charged Engine	Standard
Two-Speed Drive	Standard
<b>Operator station</b>	
Adjustable Arm Rests / Control Towers 1	Standard
Air conditioning with manual adjustment	Optional
Air suspension seat	Optional
Cab Enclosure	Optional
Dual-Hand Controls	Optional
Foot and Hand Throttles 2	Standard
Gehl T-Bar Controls	Optional
Hand/Foot Controls	Optional
Heating	Optional
High-Back Adjustable Seat	Standard
Horn	Standard
Joystick controls	Optional
ROPS/FOPS Level II Overhead Guard	Standard
Sound Reduction Material	Standard
Suspension Seat - Mechanical	Optional
<b>Other options</b>	
Hydrostatic Drive - Servo	Standard
Selectable Self-Leveling Hydraulic Lift Action 4	Optional
<b>Secondary functions</b>	
Counterweight	Standard
Full Instrumentation	Standard
Hydraglide™ Ride Control 3	Standard
<b>Security</b>	
Anti-Vandalism Protection	Standard
Back-Up Alarm	Optional
Brake Control (Auto / Manual)	Standard
Hydraloc™ Safety System	Standard
Lift Arm Support Device	Standard
Operator Restraint Bar	Standard



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes