

Technical sheet :

# 280 TJ-X

---



 **MANITOU**  
HANDLING YOUR WORLD


| Capacities                              |         | Metric   | Imperial   |
|---|---------|--|--|
| Working height                          | h21     | 27.73 m  | 91 ft  |
| Floor height (access)                   | h20     | 0.48 m   | 1 ft 7 in  |
| Platform height                         | h7      | 25.73 m  | 84 ft 5 in   |
| Max. outreach                           |         | 21.45 m  | 70 ft 4 in   |
| Pendular arm rotation (top / bottom)    |         | +56.80 ° / -62 °   | +56.80 ° / -62 °   |
| Platform capacity / capacity (maximum)  | Q       | 240 kg / 350 kg  | 529 lb / 772 lb  |
| Turret rotation                         |         | 360 °  | 360 °  |
| Platform rotation (right / left)        |         | 90 ° / 90 °  | 90 ° / 90 °  |
| Number of people (indoor / outdoor)     |         | 2 / 3  | 2 / 3  |
| Weight and dimensions                   |         |  |  |
| Platform weight*                        |         | 16650 kg   | 36707 lb   |
| Platform dimensions (length x width)    | lp / ep | 2.30 m x 0.90 m  | 7 ft 7 in x 2 ft 11 in   |
| Overall length                          | l1      | 11.36 m  | 37 ft 3 in   |
| Overall width                           | b1      | 2.48 m   | 8 ft 2 in  |
| Overall height                          | h17     | 2.73 m   | 8 ft 11 in   |
| Overall length (stowed)                 | l9      | 8.09 m   | 26 ft 7 in   |
| Overall height (stowed) **              | h18     | 2.71 m   | 8 ft 11 in   |
| Overall length with platform extension  | l15     | 11.35 m  | 37 ft 3 in   |
| Counterweight Oversize / Reach          |         | 1.45 m   | 4 ft 9 in  |
| Ground clearance at centre of wheelbase | m2      | 0.41 m   | 1 ft 4 in  |
| Wheelbase                               | y       | 2.80 m   | 9 ft 2 in  |
| Performances                            |         |  |  |
| Drive speed - stowed                    |         | 4.50 km/h  | 3 mph  |
| Drive speed - raised                    |         | 0.80 km/h  | 0.50 mph   |
| Gradeability                            |         | 34 %   | 34 %   |
| Permissible leveling                    |         | 4 °  | 4 °  |
| Wheels                                  |         |  |  |
| Drive wheels (front / rear)             |         | 2 / 2  | 2 / 2  |
| Braking wheels (front / rear)           |         | 2 / 2  | 2 / 2  |
| Engine/Battery                          |         |  |  |
| Engine brand / model                    |         | Kubota - V2403-M   | Kubota - V2403-M   |
| I.C. Engine power rating / Power        |         | 46 Hp / 34.10 kW   | 46 Hp / 34.10 kW   |
| Miscellaneous                           |         |  |  |
| Ground Pressure                         |         | 22.25 dan/cm2  | 323 PSI  |
| Hydraulic Pressure                      |         | 250 bar  | 3626 PSI   |
| Fuel tank                               |         | 72 l   | 19 US gal  |
| Vibration on hands/arms                 |         | < 0.50 m/s <sup>2</sup>  | < 0.50 m/s <sup>2</sup>  |
| Daily consumption **                    |         | 10.81 l  | 3 US gal   |
| Standards compliance                    |         |  |  |
| This machine is in compliance with:     |         | European directives: 2006/42/EC- Machinery<br>(revised EN280:2013) - 2004/108/EC (EMC) -<br>2006/95/EC (Low voltage) | European directives: 2006/42/EC- Machinery<br>(revised EN280:2013) - 2004/108/EC (EMC) -<br>2006/95/EC (Low voltage) |

\*Varies according to options and standards of the country to which the machine is delivered


\*\* According to "REDUCE cycle"

## 280 TJ-X - Load chart

Load Chart for MEWP Metric



Load Chart for MEWP (Imperial)



# Equipment

## Standard

20" tyres  
230V Predisposition  
4 simultaneous movements  
4 wheel drive  
4 wheel steer with crab mode  
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)  
Backup electrical pump  
Basket 2,300 mm  
CAN bus technology  
Continuous turret rotation  
Dead man pedal  
Differential locking on rear axle  
Electronic platform compensation  
Emergency stop button in platform and on frame  
Engine on swivel chair  
Front axle with limited slip  
Fuel gauge with low level indicator  
Hom in the platform  
Integrated diagnostic assistance  
Oscillating front axle

## Optional

110 or 230V plug with differential circuit breaker  
Additional storage boxes  
Basket 1,800 mm  
Biodegradable oil  
Catalytic cleaner  
Coded anti-start  
Cold weather protection oil  
Highly capacity battery  
Key lock on turret cover  
Lockable fuel cap  
Non-marking tyres  
On-board generator (3,5 or 5 kW)  
Refinery kit  
SMS : Safe Man System  
Safety hamess  
Screen protection on the lower box control  
Water predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes