

Technical sheet :

1050RT



Capacities		Metric	Imperial
Operating Weight		2141 kg	4720 lb
Unladen weight		1928 kg	4251 lb
Operating Capacity at 35% Tipping Load		476 kg	1049 lb
Operating Capacity At 50% Tipping Load		680 kg	1499 lb
Tipping capacity		1361 kg	3000 lb
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	3650 mm	144 in
Height to Hinge Pin - Fully Raised	h28	2769 mm	109 in
Dump reach - Full height	r6	673.10 mm	26 in
Dump angle at full height	a5	38 °	38 °
Dump Height - Fully Raised	h29	2134 mm	84 in
Maximum Rollback Angle - Fully Raised	a4	102 °	102 °
Overall Height to top of ROPS	h17	1816 mm	71 in
Overall length with bucket	l16	2985 mm	118 in
Overall Length without Bucket	l1	2258 mm	89 in
Specified Height	h31	1466 mm	58 in
Reach at Specified Height	r4	991 mm	39 in
Dump angle at specified height	a17	72 °	72 °
Carry Position	d5	127 mm	5 in
Maximum Rollback Angle at Carry Position	a14	32 °	32 °
Digging Position	h32	0 mm	0 in
Angle of Departure with STD Counterweight		35 °	35 °
Ground clearance	m4	191 mm	8 in
Track gauge	b10	1039 mm	41 in
Track Shoe Width	b20	250 mm	10 in
Crawler base	y2	1283 mm	51 in
Overall width less bucket	b1	1290 mm	51 in
Bucket Width	e1	1372 mm	54 in
Clearance Radius - Front with Bucket	b18	1854 mm	73 in
Angle of Approach	a3	90 °	90 °
Grouser Height		25 mm	0.98 in
Track Type / Track Rollers / Roller Type		Rubber / 4 / Steel	Rubber / 4 / Steel
Performances			
Ground Speed - Single Speed		10.10 km/h	6 mph
Drawbar Pull/Traction Effort		1996 kg	4400 lb
Bucket Breakout - Tilt Cylinder		1346 kg	2967 lb
Bucket Breakout - Lift Cylinder		1376 kg	3034 lb
Engine			
Engine brand		Yanmar	Yanmar
Engine model		3TNV88C-KMSV	3TNV88C-KMSV
Motor Type		Radial Piston	Radial Piston
Gross Power / Power		25.50 kW @ 2800 rpm	25.50 kW @ 2800 rpm
Net Power / Power		23.70 kW / 2800 rpm	23.70 kW / 2800 rpm
Max. torque		109.40 Nm	81 ft/lbs
I.C. Engine power rating		34.20 Hp	34.20 Hp
Battery voltage		12 V	12 V
Cold Cranking Amps at Temperature (CCA)		800 A	800 A
Alternator - Voltage / Ampere		12 V / 55 A	12 V / 55 A
Hydraulics			
Standard flow - Auxiliary hydraulics		55 l/min	15 US gpm
Tank capacities			
Oil Pan Capacity		5.87 l	2 US gal
Hydraulic tank capacity		30 l	8 US gal
Fuel tank		36 l	10 US gal
Liquid cooling tank volume		6.62 l	2 US gal
Displacement / Number of cylinders		1.64 l / 3	0.43 US gal / 3
Noise and vibration			
Noise to environment (LwA)		101 dB	101 dB
Noise at driving position (LpA)		85.80 dB	85.80 dB
Miscellaneous			
Ground Pressure		0.33 bar	5 PSI

Mechanical Lift Cylinder Lock



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes