

Technical sheet :

VJR 26

OXYGEN
by MANITOU




 **MANITOU**
HANDLING YOUR WORLD

Capacities		Imperial
Floor height (access)	h20	1 ft 8 in
Platform height	h7	25 ft 9 in
Max. outreach		10 ft 4 in
Overhang		21 ft 11 in
Pendular arm rotation (bottom)		+70 °
Platform capacity	Q	441 lb
Number of people (indoor / outdoor)		2 / 1
Weight and dimensions		
Platform weight*		5842 lb
Platform dimensions (length x width)	lp / ep	3 ft 8 in x 3 ft 1 in
Overall length	l1	9 ft 2 in
Overall width	b1	3 ft 3 in
Overall height	h17	6 ft 6 in
Jib length	l13	4 ft 11 in
External turning radius	Wa3	6 ft 10 in
Ground clearance under pothole protection	m6	1 in
Ground clearance at centre of wheelbase	m2	4 in
Performances		
Drive speed - stowed		3 mph
Drive speed - raised		0.40 mph
Gradeability		25 %
Permissible leveling		2 °
Wheels		
Standard tires		16.5-11 1/4 / 406 x 127 mm
Drive wheels (front / rear)		0 / 2
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Electric Pump		3 kW
Number of hydraulic pump / Capacity of hydraulic pump		2 x 0.26 in³
Battery voltage		24 V
Battery capacity		250 Ah
Integrated charger / charger		24 V / 30 mA
Miscellaneous		
Number of cycles with STD Battery (HIRD)		29
Ground Pressure		171 PSI
Hydraulic Pressure		2031 PSI
Hydraulic tank capacity		6 US gal
Standards compliance		
This machine is in compliance with:		ANSI A92.20-2018 CSA B354.6 ICES-002-Issue 6 Standard Canadian EMC


*Varies according to options and standards of the country to which the machine is delivered

VJR 26 - Load chart

Load Chart for MEWP (Imperial)



VJR 26 - Dimensional drawing



Equipment

Standard
110 V American plug with differential circuit breaker
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
Battery charge indicator lamp
CAN bus technology
Emergency stop button in platform and on frame
Fixed pothole protection
Fork pockets
Hom in the platform
Hour meter
Integrated diagnostic assistance
Manual emergency lowering
Multi-voltage integrated charger
Negative-type braking on rear wheels
Non-marking rubber tyres
Pendular arm
Platform with open-work floor
Proportional controls
Slings and securing rings
Tool box in platform
Traction battery

Optional
Biodegradable oil
Coded anti-start
Cold weather protection oil
Water predisposition
Working headlight in platform



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes