RS8-44 M74 RS




GEHL®

		RS8-44 M74 Created on April 25, 2024 at 8:31:25 p.m. UTC		
Capacities		Metric	Imperial	
Max. capacity		3628.73 kg	8000 lb	
Max. lifting height		13.41 m	44 ft	
Max. outreach		9.27 m	30 ft 5 in	
Weight and dimensions				
Overall length to carriage	l11	6.04 m	19 ft 10 in	
Length to face of forks	l2	5.82 m	19 ft 1 in	
Overall width	b1	2.50 m	8 ft 2 in	
Overall height	h17	2.34 m	7 ft 8 in	
Wheelbase	у	3.05 m	10 ft	
Ground clearance	m4	406 mm	16 in	
Overall cab width	b4	838 mm	33 in	
Tilt-up angle	a4	12 °	12 °	
Tilt-down angle	a5	112 °	112 °	
External turning radius	Wa3	4.17 m	13 ft 8 in	
Unladen weight		10660 kg	23501 lb	
Overall weight		10660 kg	23501 lb	
Standard tires		13 x 24	13 x 24	
Frame leveling longitudinal +/-		10 °	10 °	
Frame leveling corrector	a9	10 °	10 °	
Engine				
Engine brand		Deutz	Deutz	
Engine norm		Stage IV / Tier 4 Final	Stage IV / Tier 4 Final	
Engine model		TCD 3.6 L4	TCD 3.6 L4	
I.C. Engine power rating - Power		74 Hp / 55 kW	74 Hp / 55 kW	
Max. torque / Engine rotation		390 Nm @ 1300 rpm	288 ft/lbs @ 1300 rpm	
Transmission				
Transmission type		Torque converter with powershift gearbox	Torque converter with powershift gearbox	
Number of gears (forward / reverse)		4/3	4/3	
Max. travel speed		24 km/h	15 mph	
Parking brake		SAHR	SAHR	
Service brake		Wet disc brakes	Wet disc brakes	
Axle Manufacturer		Dana	Dana	
Hydraulics				
Hydraulic pump type		Gear pump	Gear pump	
Hydraulic flow / Pressure		157 l/min-207 bar	41 US gpm-3002 PSI	
Tank capacities			3.	
Hydraulic oil		117.35 l	31 US gal	
Fueltank		178 l	47 US gal	
Miscellaneous			3	
Steering wheels (front / rear)		2 / 2	2 / 2	
Drive wheels (front / rear)		2/2	2/2	
Safety cab homologation		ROPS/FOPS	ROPS/FOPS	
Controls		Single joystick with FNR	Single joystick with FNR	

RS8-44 M74 - Load chart

Machine on tyres with forks Imperial







Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend