

ALT950

AL/ALT



GEHL®

Capacities		Metrisch	US-System
Static tipping load with forks (straight)		4978 kg	10975 lb
Static tipping load with forks (full turn)		4147 kg	9143 lb
Max. payload with forks as per EN 474-3 (80%)		3300 kg	7275 lb
Max. lifting height (below forks)	h3	5.20 m	17 ft 1 in
Max. outreach		3.30 m	10 ft 10 in
Reach at max. height		1.20 m	3 ft 11 in
Breakout force with bucket		6730 daN	6730 daN
Static tipping load with pallet forks - Straight with cab		4978 kg	10975 lb
Weight and dimensions			
Unladen weight (with forks)		8490 kg	18717 lb
Overall length to carriage (with hitch)	l1	5.72 m	18 ft 9 in
Wheelbase	y	2.50 m	8 ft 2 in
Overall height with cab	h17	2.70 m	8 ft 10 in
Tilt-up angle	a4	9 °	9 °
Tilt-down angle	a5	156 °	156 °
External turning radius (over tyres)	Wa1	4.20 m	13 ft 9 in
Articulation angle	a19	44 °	44 °
Overall width less bucket	b1	2.29 m	7 ft 6 in
Overall length - Less Bucket	l2	5.72 m	18 ft 9 in
Standard tyres		Alliance - A580 - 460/70 R24 159A8	Alliance - A580 - 460/70 R24 159A8
Ground clearance	m4	0.39 m	1 ft 3 in
Performances			
Crowd		3.50 s	3.50 s
Dump		2.70 s	2.70 s
Engine			
Engine brand		Deutz	Deutz
Engine model		TCD 4.1 L4	TCD 4.1 L4
Number of cylinders / Capacity of cylinders		4 - 4038 cm ³	4 - 246 in ³
I.C. Engine power rating / Power (kW)		106.63 kW / 105 kW	143 Hp / 141 Hp
Max. torque / Engine rotation		550 Nm / 2300 rpm	406 ft/lbs / 2300 rpm
Engine cooling system		3 water radiators + air + hydraulic oil	3 water radiators + air + hydraulic oil
Transmission			
Transmission type		M-Varioshift	M-Varioshift
Max. travel speed (may vary according to applicable regulations)		40 km/h	25 mi/h
Travel speed (laden)		40 km/h	25 mi/h
Differential lock		Limited slip differential on front and rear axles	Limited slip differential on front and rear axles
Parking brake		Manuel	Manuel
Hydraulics			
Hydraulic pump type		Variable displacement pump	Variable displacement pump
Hydraulic flow - Pressure		158 l/min / 270 bar	42 US gpm / 3916 PSI
Tank capacities			
Hydraulic oil		150 l	40 US gal
Fuel tank		150 l	40 US gal
Diesel Exhaust fluid (AdBlue® type)		10 l	3 US gal
Noise and vibration			
Noise at driving position (LpA) tested following NF EN 12053 norm		72 dB	72 dB
Noise to environment (LwA)		107 dB	107 dB
Vibration to whole hand/arm		< 2.52 m/s ²	< 2.52 m/s ²
Miscellaneous			
Safety cab homologation		Cabin ROPS - FOPS Level 2	Cabin ROPS - FOPS Level 2



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend