

Technical sheet :

MC-X 30-2



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Imperial
1.1	Manufacturer		Manitou
1.2	Model Name		MC-X 30-2
1.3	Power source		Diesel
1.4	Operator type		Seated
1.5	Max. capacity	Q	6614 lb
1.6	Load center of gravity	c	20 in
1.8	Load distance, centre of drive axle to fork	x	25 in
1.9	Wheelbase	y	75 in
	Weight		
2.1	Service weight		9601 lb
2.2	Weight on front axle (laden) / rear axle (laden)		14187 lb / 2028 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		3660 lb / 5941 lb
	Wheels		
3.1	Tires type		Pneumatic
3.2	Dimensions of front wheels		12,5/80-18/12 SL R4
3.3	Dimensions of rear wheels		7,00-12/12 ED PLUS
3.5	Number of front wheels / rear wheels		2 / 2
3.5.2	Number of drive wheels		2
3.6	Front wheel gauge	b10	46 in
3.7	Rear wheel gauge	b11	46 in
	Dimensions		
4.7	Height of overhead guard (cabin) / Overall height of low overhead guard (Buggie version)	h6 / h6*	85 in / 78 in
4.8	Seat height/stand height	h7	43 in
4.19	Overall length	l1	168 in
4.20	Length to face of forks	l2	121 in
4.21	Overall width	b1	57 in
4.22	Forks section x width x length	s / e / l	2 in x 5 in / 45 in
4.23	Fork carriage ISO 2328 (class/form) A/B		3A
4.24	Fork carriage width	b3	50 in
4.31	Ground clearance below mast	m1	12 in
4.32	Ground clearance at centre of wheelbase	m2	12 in
4.35	Turning radius	Wa	104 in
	Performances		
5.1	Travel speed (laden / unladen)		7 mph / 15 mph
5.2	Lifting speed (laden / unladen)		2 ft/s / 2 ft/s
5.3	Lowering speed (laden / unladen)		2 ft/s / 0.98 ft/s
5.5	Drawbar pull (Laden / Unladen)		1810 daN / 1150 daN
5.7	Gradeability (laden / unladen)		23 % / 26 %
5.10	Service brake		Hydraulic brakes by loss of pressure
	Engine		
7.2	Engine power according to ISO 1585		36 kW
7.1	Engine brand / model		Kubota / V2403
7.2	Engine power according to ISO 1585		36 kW
7.3	Rated speed		2700 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 149 in³
	Miscellaneous		
8.1	Type of drive control		Cable
8.2	Working hydraulic pressure for attachments		2611 PSI
8.3	Oil flow rate for attachments		14 US gpm
8.4	Sound level at the driver's ear according to DIN 12 053		82 dB

MC-X 30-2 - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 45
Mast/fork carriage tilt, forward	°	10
Mast/fork carriage tilt, backward	°	12
h1 - Mast lowered height	in	119.6
h2 - Mast free lift	in	4.6
h3 - Mast lifting height	in	177.2
h4 - Mast extended height	in	208.3
Height at max capacity	in	98.4

Free Lift Triplex (FLT)	FLT 34	FLT 37	FLT 40	FLT 43	FLT 47	FLT 55
Mast/fork carriage tilt, forward	10	10	10	10	10	6
Mast/fork carriage tilt, backward	12	12	12	12	12	6
h1 - Mast lowered height	78.3	78.3	86.1	92	96	109.8
h2 - Mast free lift	48.6	52.6	56.5	62.4	66.3	80.1
h3 - Mast lifting height	133.9	145.7	157.5	169.3	185	216.5
h4 - Mast extended height	166.8	178.6	190.4	202.2	218	249.4
Residual capacity at max height	3483					
Height at max capacity	98.4	98.4	98.4	98.4	98.4	98.4

Full Visibility Triplex (FVT)	FVD 33	FVD 37	FVT 33
Mast/fork carriage tilt, forward	10	10	10
Mast/fork carriage tilt, backward	12	12	12
h1 - Mast lowered height	92	102.3	73.9
h2 - Mast free lift	4.6	4.6	5.1
h3 - Mast lifting height	129.9	145.7	129.9
h4 - Mast extended height	161	176.8	160.6
Height at max capacity	98.4	98.4	98.4



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes