

R105

SKID LOADERS



GEHL®

Kapazität		Metrisch	Zoll
Rated Operating Capacity		476 kg	1049 lb
Rated Operating Capacity with Optional Counterweight		533 kg	1175 lb
Eigengewicht		1905 kg	4200 lb
Gewicht und Abmessungen			
Overall Operating Height - Fully Raised	h27	3607 mm	142 in
Höhe bis Schaufeldrehpunkt – bei max. Hubhöhe	h28	2731 mm	108 in
Overall Height to Top of ROPS	h17	1784 mm	70 in
Auskippwinkel bei voller Hubhöhe	a5	40 °	40 °
Dump height	h29	2083 mm	82 in
Overall length with bucket	l16	2997 mm	118 in
Dump reach - Full height	r6	641 mm	25 in
Einkippwinkel auf Standebene	a13	31 °	31 °
Seat to ground height	h30	826 mm	33 in
Radstand	y	876 mm	34 in
Overall width less bucket	b1	1232 mm	49 in
Schaufelbreite	e1	1372 mm	54 in
Bodenfreiheit der Maschine	m4	159 mm	6 in
Overall length - Less Bucket	l2	2248 mm	89 in
Clearance Radius - Front with Bucket	b18	1829 mm	72 in
Wendekreis - vorne ohne Schaufel	b19	1067 mm	42 in
Clearance Circle - Rear	wa1	1372 mm	54 in
Leistung			
Fahrgeschwindigkeit (unbeladen)		8.26 km/h	5 mi/h
Reifen			
Standard tyres		27x8.5x15 HD	27x8.5x15 HD
Motor			
Marke		Yanmar	Yanmar
Motor Modell		3TNV88C-KMSV Stage V	3TNV88C-KMSV Stage V
Motornorm		Stage V	Stage V
Gross Power (kW)		25.50 kW	34 Hp
Net Power (kW)		23.70 kW	32 Hp
Max. Drehmoment / Motordrehzahl		109.40 Nm / 1820 rpm	81 ft/lbs / 1820 rpm
Batterie		12 V	12 V
Starter (kW)		2.30 kW	3 Hp
Hydraulisch			
Zusatzhydraulik		55 l/min	15 US gpm
Tankkapazität			
Kapazität des Kraftstoffbehälters		43.18 l	11 US gal
Reservoir Capacity Hydraulics		30.30 l	8 US gal
Hubraum		1.64 l	0.43 US gal
Lärm und Vibrationen			
Umgebungsgeräusch (LwA)		101 dB	101 dB
Ganzkörper Schwingungen (ISO 2631 - 1)		1.12 m/s ²	1.12 m/s ²
Vibrationswert an Händen/Armen		< 1.70 m/s ²	< 1.70 m/s ²



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend