

Technical sheet :


MI 35 D



 **MANITOU**
HANDLING YOUR WORLD

| | Technical characteristics | | Imperial |
|-------|---|-----------|------------------------|
| 1.1 | Manufacturer | | Manitou |
| 1.2 | Model Name | | MI 35 D |
| 1.3 | Power source | | Diesel |
| 1.4 | Operator type | | Sitting |
| 1.5 | Max. capacity | Q | 7716 lb |
| 1.6 | Load center of gravity | c | 20 in |
| 1.8 | Load distance, centre of drive axle to fork | x | 19 in |
| 1.9 | Wheelbase | y | 67 in |
| | Weight | | |
| 2.1 | Service weight | | 10714 lb |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 16226 lb / 2205 lb |
| 2.3 | Weight on front axle (Unladen) / rear axle (Unladen) | | 4023 lb / 6691 lb |
| | Wheels | | |
| 3.1 | Tires type | | PPS |
| 3.2 | Dimensions of front wheels | | 28-9-1512 |
| 3.3 | Dimensions of rear wheels | | 6.50-10 10 |
| 3.5 | Number of front wheels / rear wheels | | 2 / 2 |
| 3.5.2 | Number of drive wheels | | 2 |
| 3.6 | Front wheel gauge | b10 | 40 in |
| 3.7 | Rear wheel gauge | b11 | 38 in |
| | Dimensions | | |
| 4.7 | Height of overhead guard (cabin) | h6 | 84 in |
| 4.8 | Seat height/stand height | h7 | 48 in |
| 4.12 | Height of towing bar (coupling height) | h10 | 14 in |
| 4.19 | Overall length | l1 | 155 in |
| 4.20 | Length to face of forks | l2 | 110 in |
| 4.21 | Overall width | b1 | 48 in |
| 4.21 | Overall width - Single wheels | b1 | 48 in |
| 4.22 | Forks section / width / length | s / e / l | 2 in x 5 in x 45 in |
| 4.23 | Fork carriage ISO 2328 (class/form) A/B | | 3A |
| 4.24 | Fork carriage width | b3 | 43 in |
| 4.31 | Ground clearance below mast | m1 | 5 in |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 8 in |
| 4.33 | Aisle Width for pallets 1000 x 1200 crossways | Ast | 165 in |
| 4.34 | Aisle width for 800 x 1200 pallet lengthways | Ast | 173 in |
| 4.36 | Internal turning radius (over tyres) | b13 | 6 in |
| | Performances | | |
| 5.1 | Travel speed (laden / unladen) | | 11 mph-11 mph |
| 5.2 | Lifting speed (laden / unladen) | | 1 ft/s-1 ft/s |
| 5.3 | Lowering speed (laden / unladen) | | 1 ft/s-1 ft/s |
| 5.5 | Drawbar pull (Laden / Unladen) | | 1830 daN / 1520 daN |
| 5.7 | Gradeability (laden / unladen) | | 18 % / 20 % |
| 5.10 | Service brake | | Hydraulic |
| | Engine | | |
| 7.1 | Engine brand / model | | Yanmar / 4TNV94L-BXPHZ |
| 7.2 | Engine power according to ISO 1585 | | 35 kW |
| 7.3 | Rated speed | | 2400 rpm |
| 7.4 | Number of cylinders / Capacity of cylinders | | 4 - 186 in³ |
| | Miscellaneous | | |
| 8.2 | Working hydraulic pressure for attachments | | 2321 PSI |
| 8.3 | Oil flow rate for attachments | | 18 US gpm |
| 8.4 | Measured/guaranteed mean noise level at the ear of the operator | | < 84 dB |
| 8.4 | Sound level at the driver's ear according to DIN 12 053 | | 84 dB |

MI 35 D - Dimensional drawing



Characteristics of masts and residual capacities

| Full Visibility Duplex (FVD) | | FVD 33 | FVD 37 | FVD 40 |
|---|----|--------|--------|--------|
| Mast/fork carriage tilt, forward | ° | 6 | 6 | 6 |
| Mast/fork carriage tilt, backward | ° | 12 | 12 | 12 |
| h1 - Mast lowered height | in | 91.1 | 101 | 106.9 |
| h2 - Mast free lift | in | 5.7 | 5.7 | 5.7 |
| h3 - Mast lifting height | in | 129.9 | 145.7 | 157.5 |
| h4 - Mast extended height | in | 162 | 177.8 | 189.6 |
| Residual capacity at max height | lb | 7716 | 7716 | 7716 |
| Residual capacity with integrated side shift at max heighth | lb | 7716 | 7716 | 7716 |
| Height at max capacity | in | 129.9 | 145.7 | 157.5 |
| Height at max capacity with integrated sideshift | in | 129.9 | 145.7 | 157.5 |

| Free Lift Duplex (FLD) | | FLD 33 | FLD 37 | FLD 40 |
|---|----|--------|--------|--------|
| Mast/fork carriage tilt, forward | ° | 6 | 6 | 6 |
| Mast/fork carriage tilt, backward | ° | 12 | 12 | 12 |
| h1 - Mast lowered height | in | 91.7 | 99.6 | 105.5 |
| h2 - Mast free lift | in | 59.1 | 66.9 | 72.8 |
| h3 - Mast lifting height | in | 129.9 | 145.7 | 157.5 |
| h4 - Mast extended height | in | 162.6 | 178.3 | 190.2 |
| Residual capacity at max height | lb | 7716 | 7716 | 7716 |
| Residual capacity with integrated side shift at max heighth | lb | 7716 | 7716 | 7716 |
| Height at max capacity | in | 129.9 | 145.7 | 157.5 |
| Height at max capacity with integrated sideshift | in | 129.9 | 145.7 | 157.5 |

| Free Lift Triplex (FLT) | | FLT 43 | FLT 45 | FLT 47 | FLT 48 | FLT 50 | FLT 55 | FLT 60 | FLT 65 |
|---|----|--------|--------|--------|--------|--------|--------|--------|--------|
| Mast/fork carriage tilt, forward | ° | 6 | 6 | 6 | 6 | 6 | 3 | 3 | 3 |
| Mast/fork carriage tilt, backward | ° | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 |
| h1 - Mast lowered height | in | 87.2 | 89.2 | 91.1 | 93.1 | 95.1 | 101 | 110.8 | 116.7 |
| h2 - Mast free lift | in | 54.5 | 56.5 | 58.5 | 60.4 | 62.4 | 68.3 | 78.1 | 84.1 |
| h3 - Mast lifting height | in | 169.3 | 177.2 | 185 | 189 | 196.9 | 216.5 | 236.2 | 255.9 |
| h4 - Mast extended height | in | 202 | 211.8 | 217.7 | 221.7 | 229.5 | 249.2 | 270.9 | 288.6 |
| Residual capacity at max height | lb | 7606 | 7496 | 7275 | 7275 | 6614 | 4850 | 3527 | 3307 |
| Residual capacity with integrated side shift at max heighth | lb | 7606 | 7275 | 7055 | 7055 | 6393 | 4630 | 3307 | 3086 |
| Height at max capacity | in | 157.5 | 157.5 | 157.5 | 157.5 | 157.5 | 157.5 | 157.5 | 157.5 |
| Height at max capacity with integrated sideshift | in | 157.5 | 157.5 | 157.5 | | | | | |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes