

Technical sheet :

# 170 AETJ-L BI

---




 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Metric
Working height	h21	17.03 m
Platform height	h7	15.03 m
Max. outreach		9.43 m
Overhang		7.27 m
Pendular arm rotation (top / bottom)		+62 ° / -59 °
Platform capacity	Q	230 kg
Turret rotation		355 °
Platform rotation (right / left)		70 ° / 70 °
Number of people (indoor / outdoor)		2 / 2
Weight and dimensions		
Platform weight*		7435 kg
Platform dimensions (length x width)	lp / ep	1.20 m x 0.92 m
Floor height (access)	h20	0.40 m
Overall length	l1	6.99 m
Overall width	b1	1.91 m
Overall height	h17	2.10 m
Overall length (stowed)	l9	5.27 m
Overall height (stowed)	h18 ***	2.13 m
Jib length	l13	1.26 m
Counterweight offset (turret at 90°)	a7	0 m
External turning radius	Wa3	4.27 m
Ground clearance at centre of wheelbase	m2	0.18 m
Wheelbase	y	2.20 m
Performances		
Drive speed - stowed		6 km/h
Drive speed - raised		0.60 km/h
Gradeability		21 %
Permissible leveling		5 °
Wheels		
Tires type		Foam Filled Non Marking
Drive wheels (front / rear)		0 / 2
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Electric engine power rating		2 x 4.50 kW
Lift motor power		3.70 kW
I.C. Engine power rating / Power		12 Hp / 9.20 kW
Battery voltage		48 V
Battery nominal voltage / capacity		48 V / 300 Ah
Battery energy		14 kWh
On-board charger (V / A)		48 V / 45 A
Miscellaneous		
Ground Pressure		14.48 dan/cm <sup>2</sup>
Hydraulic Pressure		200 bar
Hydraulic tank capacity		12 l
Fuel tank		30 l
Vibration on hands/arms		< 2.50 m/s <sup>2</sup>
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)

# 170 AETJ-L BI - Load chart

Load Chart metric



# 170 AETJ-L BI - Dimensional drawing



# Equipment

---

## Standard

230V Predisposition  
All-terrain, non-marking, foam-filled tyres  
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)  
Battery charge indicator lamp  
CAN bus technology  
Easy Manager  
Emergency stop button in platform and on frame  
Horn in the platform  
Hour meter  
Integrated diagnostic assistance  
Manual emergency lowering  
Multi-voltage integrated charger  
Negative-type braking on rear wheels  
Pendular arm  
Platform with open-work floor  
Proportional controls  
Protective cover for control panel  
Slings and securing rings  
Tool box in platform  
Traction battery  
Travel possible at maximum height

## Optional

110 or 230V plug with differential circuit breaker  
Biodegradable oil  
Cold weather protection oil  
LED strobe Light on the basket  
LED strobe light on the turret  
Lights  
Lockable fuel cap  
Personalized paintwork  
SMS : Safe Man System  
Safety harness  
Water predisposition  
Working headlight in platform



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes