

Ficha técnica :

170 AETJ-L BI




 **MANITOU**
HANDLING YOUR WORLD


Capacities		Métrico
Working height	h21	17.03 m
Floor height (access)	h20	0.40 m
Platform height	h7	15.03 m
Max. outreach		9.43 m
Overhang		7.27 m
Pendular arm rotation (top / bottom)		+62 ° / -59 °
Platform capacity	Q	230 kg
Turret rotation		355 °
Platform rotation (right / left)		70 ° / 70 °
Number of people (indoor / outdoor)		2 / 2
Weight and dimensions		
Platform weight*		7435 kg
Platform dimensions (length x width)	lp / ep	1.20 m x 0.92 m
Overall length	l1	6.99 m
Overall width	b1	1.91 m
Overall height	h17	2.10 m
Overall length (stowed)	l9	5.27 m
Overall height (stowed) **	h18	2.13 m
Jib length	l13	1.26 m
Counterweight offset (turret at 90°)	a7	0 m
External turning radius	Wa3	4.27 m
Ground clearance at centre of wheelbase	m2	0.18 m
Wheelbase	y	2.20 m
Performances		
Drive speed - stowed		6 km/h
Drive speed - raised		0.60 km/h
Gradeability		21 %
Permissible leveling		5 °
Wheels		
Tires type		Foam Filled Non Marking
Drive wheels (front / rear)		0 / 2
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Electric engine power rating		2 x 4.50 kW
Electric Pump		3.70 kW
I.C. Engine power rating / Power		12 Hp / 9.20 kW
Battery voltage		48 V
Battery nominal voltage / capacity		48 V / 300 Ah
Battery energy		14 kWh
Integrated charger / charger		48 V / 45 A
Miscellaneous		
Ground Pressure		14.48 dan/cm2
Hydraulic Pressure		200 bar
Hydraulic tank capacity		12 l
Fuel tank		30 l
Vibration on hands/arms		< 2.50 m/s²
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)

170 AETJ-L BI - Diagramas de carga

Load Chart metric



170 AETJ-L BI - Diagrama dimensional



Equipamiento

Estándar
230V Predisposition
All-terrain, non-marking, foam-filled tyres
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
Battery charge indicator lamp
CAN bus technology
Easy Manager
Emergency stop button in platform and on frame
Hom in the platform
Hour meter
Integrated diagnostic assistance
Manual emergency lowering
Multi-voltage integrated charger
Negative-type braking on rear wheels
Pendular arm
Platform with open-work floor
Proportional controls
Protective cover for control panel
Slinging and securing rings
Tool box in platform
Traction battery
Travel possible at maximum height

Opcional
110 or 230V plug with differential circuit breaker
Biodegradable oil
Cold weather protection oil
Lights
Lockable fuel cap
Personalized paintwork
SMS : Safe Man System
Safety harness
Water predisposition
Working headlight in platform



Oficina Central

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - Francia

Tel.: 00 33 (0)2 40 09 10 11 - Fax: 00 33 (0)2 40 09 10 97

www.manitou.com



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

Manitou BF SA - Sociedad anónima con Consejo de Administración - Capital social: 39 668 399 euros - 857 802 508 RCS Nantes