

Technical sheet :

CRANE SKIP





Benefits







- Versatile: hitch on forks or suspended.
- Attachment's center of gravity designed for a great stability.
- Optimized shape for efficient distribution.
- Reviewed design maximizing operator safety & component protection.
- Optional: hydraulic opening ("H") for an accurate and controlled distribution.

Technical characteristics

- Fork locking system.
- 3 way forks entry (fork sleeves 170 x 75 mm).
- Hydraulic opening available on the 600 H version.
- Protected hydraulic components.
- Discharged width: 540 mm.
- GL 600 H for MRT: equipped with a counterbalance valve.

Technical characteristics		GL 400	GL 600	GL 600 H	GL 600 H MRT
Distance to center of gravity (in)		1' 3"	1' 6"	1' 5"	-
Capacities					
Capacity (lbs)		2116.44	3174.66	3174.66	-
Heaped Capacity (US gal)		105.67	158.50	158.50	-
Weight and dimensions					
Overall height (in)	h17	3' 10"	3' 11"	3' 11"	-
Width (in)		3' 9"	4' 6"	4' 4"	4' 4"
Length (in)		2' 10"	3' 3"	3' 3"	-
Overall weight (lbs)		407.86	500.45	531.31	531.31
Working Parameters					
Machine Equipement		✕	✕		
Opening		Manual	Manual	Hydraulic	Hydraulic
Flexible tube		No	No	No	No
Machines compatibility		GL 400	GL 600	GL 600 H	GL 600 H MRT
Reference number		52000527	52000528	52000529	52553617
MRT 1645 75		-	-	X	-
MRT 1645 115		-	-	X	-
MRT 1845 75		-	-	X	-
MRT 1845 115		-	-	X	-
MRT 2145 115		-	-	X	-
MRT 2260		-	-	X	-
MRT 2545 115		-	-	X	-
MRT 2570		-	-	X	-
MRT 2660		-	-	X	-
MRT 3060		-	-	X	-
MRT 3570		-	-	X	-
MRT 3570 ES		-	-	X	-
MRT-X 1645		-	-	X	-
MRT-X 1845		-	-	X	-
MRT-X 2145		-	-	X	-
MRT-X 2260		-	-	X	-
MRT-X 2545		-	-	X	-
MRT-X 2570		-	-	X	-
MRT-X 2660		-	-	X	-
MRT-X 3060		-	-	X	-
MRT-X 3570		-	-	X	-
MRT-X 3570 ES		-	-	X	-
MT 625 HA		X	X	X	-
MT 733 Easy		X	X	X	-
MT 933 Easy		-	X	X	-
MT 1033 easy		X	X	X	-
MT 1440		X	X	X	-
MT 1440 A		X	X	X	-
MT 1440 HA		X	X	X	-
MT 1840		X	X	X	-
MT 1840 A		X	X	X	-
MT 1840 HA		X	X	X	-
MT-X 625 H		X	X	X	-
MT-X 1440		X	X	X	-
MT-X 1440 A		X	X	X	-
MT-X 1840		X	X	X	-
MT-X 1840 A		X	X	X	-
Reference number E-RECO		-	-	52553617	-
MRT 1640 Easy T4 S2 360°		-	-	-	X
MRT 1840 Easy T4 S2 360°		-	-	-	X
MRT 1840 Easy T4 S2 400°		-	-	-	X
MRT 2145 Easy T4 S2 360°		-	-	-	X
MRT 2145 Easy T4 S2 400°		-	-	-	X
MRT 2150 Privilege Plus		-	-	-	X
MRT 2470 Privilege Plus		-	-	-	X
MRT 2545 Easy T4 S2 360°		-	-	-	X
MRT 2545 Easy T4 S2 400°		-	-	-	X
MRT 2550 Privilege Plus		-	-	-	X
MRT 3050 Privilege Plus		-	-	-	X
MRT-X 1440 Easy 400°		-	-	-	X
MRT-X 1640 Easy 360°		-	-	-	X
MRT-X 1640 Easy 400°		-	-	-	X
MRT-X 1840 Easy 360°		-	-	-	X
MRT-X 1840 Easy 400°		-	-	-	X
MRT-X 2145 Easy 360°		-	-	-	X
MRT-X 2145 Easy 400°		-	-	-	X
MRT-X 2150 Privilege Plus		-	-	-	X
MRT-X 2470 Privilege Plus		-	-	-	X
MRT-X 2545 Easy 360°		-	-	-	X

Machines compatibility	GL 400	GL 600	GL 600 H	GL 600 H MRT
MRTX 2545 Easy 400°	-	-	-	X
MRTX 2550 Privilege Plus	-	-	-	X
MRTX 3050 Privilege Plus	-	-	-	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes