

Technical sheet :

PIPE HANDLER





Benefits

- Increases working safety & output on all pipe-handling applications.
- Perfect upholding of pipes thanks to its mobile grapple with hydraulic tine pads- increased safety on rough terrain.
- "Appendix" at the end of the grapple, ensures complete closing & prevents the pipes from sliding away.
- Separated control of grapple & tine pads for more accuracy.
- Increased polyvalence: can be used to handle other loads.

Technical characteristics

- Maximum capacity 14000 kg / 30865 lbs.
- Max. pipe diameter 1016 mm / 40".
- Increased component protection for less downtimes.
- Complete grapple opening, increased efficiency when loading palletized loads.
- Rubber-covered tine pads.
- Fork dimensions: 120 x 240 x 2400 mm / 4.7 x 9.4 x 94.5".
- Thinner forks (90 mm) available upon request.
- Forks can be used in floating or fixed mode.

Technical characteristics		PH 2100 / 8000	PH 2500 / 14000
Distance to center of gravity (in)		1' 11"	2' 11"
Capacities			
Capacity (lb)		17636.98	30864.72
Weight and dimensions			
Overall length (in)	l1	7'	9' 5"
Forks width X Forks length X Forks section (in)	e	4' 11"	9' X 7' 10" X 5"
Overall height (in)	h17	4' 7"	6' 5"
Opened grab height (in)	h34	10' 9"	15' 5"
Closed grab height (in)	h33	4' 7"	6' 5"
Width (in)		6' 11"	8'
Overall weight (lb)		4850.17	8377.57
Diameter minimum / Diameter maximum (in)		0" / 2' 9"	0" / 3' 4"

Working Parameters			
Machine Equipment			
Hydraulic system		Yes	Yes
Opening minimum (in)		0"	0"
Opening maximum (in)		2' 9"	3' 4"

Machines compatibility	PH 2100 / 8000	PH 2500 / 14000
Reference number E-RECO	939231	939332
MHT 790 ST5	X	X
MHT 12330	X	X
MHT-X 790	X	X
MHT-X 790 ST3A	X	-
MHT-X 10130	X	X
MHT-X 10180	-	X
MHT-X 10230	-	X
MHT 790 OLD	X	X
MHT 10130 OLD	X	X
MHT 10180 OLD	-	X
MHT 10230 OLD	-	X









On demand compatibility is available: For more information, contact your dealer		
MHT 12330	-	
MHT-X 12330	-	

TABLE SYMBOL

	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39 547 824 euros - 857 802 508 RCS Nantes