

Technical sheet :

MI 80 D



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Imperial
1.1	Manufacturer		Manitou
1.2	Model Name		MI 80 D
1.3	Power source		Diesel
1.4	Operator type		Seated
1.5	Max. capacity	Q	17637 lb
1.6	Load center of gravity	c	24 in
1.8	Load distance, centre of drive axle to fork	x	27 in
1.9	Wheelbase	y	102 in
	Weight		
2.1	Service weight		27646 lb
2.2	Weight on front axle (laden) / rear axle (laden)		40433 lb / 4850 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		11420 lb / 16226 lb
	Wheels		
3.1	Tires type		Pneumatic
3.2	Dimensions of front wheels		9.00-20-14PR
3.3	Dimensions of rear wheels		9.00-20-14PR
3.5	Number of front wheels / rear wheels		4 / 2
3.5.2	Number of drive wheels		4
3.6	Front wheel gauge	b10	64 in
3.7	Rear wheel gauge	b11	67 in
	Dimensions		
4.7	Height of overhead guard (cabin)	h6	102 in
4.8	Seat height/stand height	h7	59 in
4.12	Height of towing bar (coupling height)	h10	33 in
4.19	Overall length	l1	218 in
4.20	Length to face of forks	l2	158 in
4.21	Overall width	b1	85 in
4.21	Overall width - Twinned wheels	b1	85 in
4.22	Forks section / width / length	s / e / l	3 in x 6 in x 60 in
4.23	Fork carriage ISO 2328 (class/form) A/B		4A
4.24	Fork carriage width	b3	67 in
4.31	Ground clearance below mast	m1	7 in
4.32	Ground clearance at centre of wheelbase	m2	13 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	223 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	228 in
4.35	Turning radius	Wa	145 in
4.36	Internal turning radius (over tyres)	b13	52 in
	Performances		
5.1	Travel speed (laden / unladen)		15 mph-16 mph
5.2	Lifting speed (laden / unladen)		1 ft/s-1 ft/s
5.3	Lowering speed (laden / unladen)		1 ft/s-1 ft/s
5.5	Drawbar pull (Laden / Unladen)		8600 daN / 5070 daN
5.7	Gradeability (laden / unladen)		35 % / 35 %
5.10	Service brake		Hydraulic
	Engine		
7.1	Engine brand / model		Deutz / TCD 3.6
7.2	Engine power according to ISO 1585		85 kW
7.3	Rated speed		2200 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 220 in³
	Miscellaneous		
8.2	Working hydraulic pressure for attachments		2828 PSI
8.3	Oil flow rate for attachments		17 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 84 dB
8.4	Sound level at the driver's ear according to DIN 12 053		84 dB

MI 80 D - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 33	FVD 36	FVD 40	FVD 45	FVD 50
Mast/fork carriage tilt, forward	°	6	6	6	6	6	6
Mast/fork carriage tilt, backward	°	12	12	12	12	6	6
h1 - Mast lowered height	in	106.3	112.2	118.1	126	137.8	147.6
h2 - Mast free lift	in	7.9	7.9	7.9	7.9	7.9	7.9
h3 - Mast lifting height	in	118.1	129.9	141.7	157.5	177.2	196.9
h4 - Mast extended height	in	165.7	177.6	189.4	205.1	224.8	244.5
Residual capacity at max height	lb	17637	17637	17637	17637	17637	17637
Height at max capacity	in	118.1	129.9	141.7	157.5	177.2	196.9

Free Lift Triplex (FLT)		FLT 45	FLT 48	FLT 50	FLT 55	FLT 60
Mast/fork carriage tilt, forward	°	6	6	6	3	3
Mast/fork carriage tilt, backward	°	6	6	6	6	6
h1 - Mast lowered height	in	108.3	112.2	116.1	122	128
h2 - Mast free lift	in	58.5	62.4	63	70.9	78.1
h3 - Mast lifting height	in	177.2	189	196.9	216.5	236.2
h4 - Mast extended height	in	227.4	239.2	250.4	268.1	286.4
Residual capacity at max height	lb	15432	15432	14330	13448	12346
Height at max capacity	in	177.2	189	196.9	216.5	236.2



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes