

# V330

# SKID LOADERS



# GEHL®

Kapazität		Metrisch	Zoll
Rated Operating Capacity		1497 kg	3300 lb
Eigengewicht		4123 kg	9090 lb
Gewicht und Abmessungen			
Overall Operating Height - Fully Raised	h27	4369 mm	172 in
Höhe bis Schaufeldrehpunkt – bei max. Hubhöhe	h28	3332 mm	131 in
Overall Height to Top of ROPS	h17	2083 mm	82 in
Auskipppinkel bei voller Hubhöhe	a5	42 °	42 °
Dump height	h29	2502 mm	99 in
Overall length with bucket	l16	3874 mm	153 in
Dump reach - Full height	r6	813 mm	32 in
Einkippwinkel auf Standebene	a13	29 °	29 °
Seat to ground height	h30	1041 mm	41 in
Radstand	y	1257 mm	49 in
Overall width less bucket	b1	1819 mm	72 in
Schaufelbreite	e1	1880 mm	74 in
Bodenfreiheit der Maschine	m4	229 mm	9 in
Overall length - Less Bucket	l2	3023 mm	119 in
Clearance Radius - Front with Bucket	b18	2400 mm	94 in
Wendekreis - vorne ohne Schaufel	b19	1422 mm	56 in
Clearance Circle - Rear	wa1	1765 mm	69 in
Leistung			
Travel Speed with Two-Speed Option - Maximum		20.10 km/h	12 mi/h
Fahrtgeschwindigkeit (unbeladen)		13.50 km/h	8 mi/h
Reifen			
Standard tyres		14.00x17.5 HD	14.00x17.5 HD
Motor			
Marke		Yanmar	Yanmar
Motor Modell		4TNV98CT Stage V	4TNV98CT Stage V
Motornorm		Stage V	Stage V
Gross Power (kW)		53.70 kW	72 Hp
Net Power (kW)		52.70 kW	71 Hp
Max. Drehmoment / Motordrehzahl		294.20 Nm / 1625 rpm	217 ft/lbs / 1625 rpm
Batterie		12 V	12 V
Starter (kW)		3 kW	4 Hp
Hydraulisch			
Zusatzhydraulik		88.99 l/min	24 US gpm
High-Flow Auxiliary Hydraulics – Option		132 l/min	35 US gpm
Tankkapazität			
Kapazität des Kraftstoffbehälters		92.70 l	24 US gal
Reservoir Capacity Hydraulics		40 l	11 US gal
Hubraum		3.30 l	0.87 US gal
Lärm und Vibrationen			
Umgebungsgeräusch (LwA)		101 dB	101 dB
Ganzkörper Schwingungen (ISO 2631 - 1)		1.07 m/s <sup>2</sup>	1.07 m/s <sup>2</sup>
Vibrationswert an Händen/Armen		< 1.50 m/s <sup>2</sup>	< 1.50 m/s <sup>2</sup>



# GEHL®

Siège Social

P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095

Tel: (262) 334-9461 - Fax: (262) 338-7517

[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend