

Technical sheet :

# **MLT 733-115 LSU ST4**

---



 **MANITOU**  
HANDLING YOUR WORLD

Capacities		Imperial
Max. capacity	Q	7275 lb
Max. lifting height	h3	22 ft 8 in
Max. outreach		12 ft 10 in
Reach at max. height		2 ft 11 in
Breakout force with bucket		5770 daN
Weight and dimensions		
Unladen weight (with forks)		15465 lb
Ground clearance	m4	1 ft 5 in
Wheelbase	y	9 ft 3 in
Overall length to carriage (with hitch)	l11	15 ft 11 in
Front overhang		4 ft
Overall width	b1	7 ft 10 in
Overall cab width	b4	3 ft 1 in
Overall height	h17	7 ft 10 in
Tilt-down angle	a5	134 °
Tilt-up angle	a4	13 °
External turning radius (over tyres)	Wa1	12 ft 10 in
Standard tires		Alliance - A580 - 460/70 R24 159A8
Drive wheels (front / rear)		2 / 2
Steering wheels (front / rear)		2 / 2
Performances		
Lifting		6.75 s
Lowering		5.65 s
Extension		6.50 s
Retraction		3.90 s
Crowd		3.15 s
Dump		2.55 s
Engine		
Engine brand		Deutz
Engine norm		Stage IV
Engine model		TCD 3.6 l
Number of cylinders - Capacity of cylinders		4 - 221 in³
I.C. Engine power rating / Power		116 Hp / 85 kW
Max. torque / Engine rotation		302 ft/lbs @1600 rpm
Drawbar pull (Laden)		7400 daN
Reversible fan		Option
Engine cooling system		4 radiators (water + intercooler + hydraulic oil + transmission oil)
Transmission		
Transmission type		Torque converter
Gearbox		Powershuttle
Number of gears (forward / reverse)		4 / 4
Max. travel speed (may vary according to applicable regulations)		20 mph
Differential lock		Limited slip differential on front axle
Parking brake		Manual
Service brake		Oil-immersed multi-discs on front & rear axles
Hydraulics		
Hydraulic pump type		Variable displacement pump
Hydraulic flow - Pressure		40 US gpm - 3916 PSI
Flow sharing distributor		Standard
Tank capacities		
Hydraulic oil		36 US gal
Fuel tank		32 US gal
Diesel Exhaust fluid (AdBlue® type)		3 US gal
Noise and vibration		
Noise at driving position (LpA) tested following NF EN 12053 nom		76 dB
Noise to environment (LwA)		105 dB
Vibration to whole hand/arm		< 2.50 m/s²
Miscellaneous		
Tractor homologation		Tractor homologation
Safety cab homologation		ROPS - FOPS level 2 cab
Controls		JSM

## Options / Finishing

S : Standard / O : Optional / - : Not available

	Classic	Premium
<b>Lifting function</b>		
Easy Connect System (ECS)	S	S
Electrovalve for 2 hydraulic functions (on boom head)	O	O
Hydraulic attachment locking	O	O
Return pipe to hydraulic oil tank	O	O
<b>Operator station</b>		
"Active CRC" boom suspension	O	O
Air conditioning with automatic adjustment	O	O
Air conditioning with manual adjustment	O	S
Air suspension cloth-covered seat (GRAMMER)	O	S
Bluetooth USB car radio with extra microphone (100 W)	O	O
Bluetooth USB car radio with integrated microphone (100 W)	O	S
Extra front wiper	O	S
Harmony screen	S	S
Lateral wiper	O	O
Low frequency air suspension cloth seat with heating	O	O
Mechanical cloth-covered seat (GRAMMER)	S	-
Tuner car radio (50 W)	S	-
<b>Motorization/Power</b>		
Continuous flow hydraulics	O	O
Self cleaning air prefilter	S	S
<b>Secondary functions</b>		
1 pair of pre-fitted Double Action rear hydraulic couplers	O	O
Additional fuel tank (25 l)	O	O
Automatic rotating towing hitch on counterweight	O	O
Ladder hitch with choice of hooks	O	O
<b>Lighting</b>		
Boom Work Lights (on fixed part) (x2)	O	O
Front and rear LED work lights on cab (x4 : 2 front + 2 rear)	O	S
Front and rear work lights on cab (x4)	S	-
<b>Security</b>		
Audio warning on reverse	O	O



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes