

Technical sheet :

SNOW BLADE (COMPACT MACHINES)



Customer benefits

- Efficient snow removal in one go.

Technical characteristics

- 30° hydraulic orientation, 2 cylinders.
- Strong construction with shock absorber & horizontal self leveling.

[The 3D picture at the top of this page is the reference BLS 1650 / 900 - N51502221].

 **ATTACHMENTS**

Weight		BLS 1500	BLS 1500 / 900 (b)	BLS 1650 / 900	BLS 1800	BLS 1800 / 900	BLS 2100 / 900 (a)	BLS 2100 / 900 (b)	BLS 2400 / 900 (a)	BLS 2700 / 900
Overall weight (lb)		485	485	551	617	617	772	772	904	992
Weight and dimensions										
Overall height (in)	h17	2' 4"	2' 4"	2' 4"	2' 4"	2' 4"	2' 4"	2' 4"	2' 7"	2' 7"
Width (in)		4' 11"	4' 11"	5' 5"	5' 11"	5' 11"	6' 11"	6' 11"	7' 10"	8' 10"
Depth (in)	p5	2' 11"	2' 11"	2' 11"	2' 11"	2' 11"	2' 11"	2' 11"	2' 11"	2' 11"
Working Parameters										
Machine Equipment										
Horizontal angle (°)		30	30.30	30.30	30.30	30.30	30.30	30.30	30.30	30.30
Working width - angled (in)		4' 3"	4' 3"	4' 7"	5' 1"	5' 1"	6'	6'	6' 10"	7' 8"

Machines compatibility	BLS 1500	BLS 1500 / 900 (b)	BLS 1650 / 900	BLS 1800	BLS 1800 / 900	BLS 2100 / 900 (a)	BLS 2100 / 900 (b)	BLS 2400 / 900 (a)	BLS 2700 / 900
All-Tach® Namow	N51502219	-	-	-	-	-	-	-	-
All-Tach®	-	N51502220	N51502221	N51502224	N51502224	N51502225	N51502226	N51502227	N51502320
4 point Carriage	N51502217	-	52741074	N51502222	-	-	-	-	-
Euro Carriage	N51502218	-	52741072	N51502223	-	-	-	-	-
1050R	-	X	X	-	-	-	-	-	-
1050RT	-	X	X	-	-	-	-	-	-
1350R NXT2	-	-	-	-	X	-	-	-	-
1350RT	-	-	-	X	-	-	-	-	-
1640 E	X	-	-	-	-	-	-	-	-
1650R	-	-	-	-	-	X	-	-	-
1650RT	-	-	-	-	-	X	-	-	-
1850RT	-	-	-	-	-	-	X	-	-
1900R	-	-	-	-	-	X	-	-	-
2100V	-	-	-	X	-	X	-	-	-
2100VT	-	-	-	-	-	-	X	-	-
2150RT	-	-	-	-	-	-	-	X	-
2200R	-	-	-	-	-	X	-	-	-
2300V	-	-	-	-	-	X	-	-	-
2300VT	-	-	-	-	-	-	-	X	-
2600R	-	-	-	-	-	-	-	X	-
2700V NXT2	-	-	-	-	-	X	-	-	-
2750V	-	-	-	-	-	X	-	X	-
2750VT	-	-	-	-	-	-	-	X	-
3300V NXT2	-	-	-	-	-	-	-	X	-
4200V	-	-	-	-	-	-	-	-	X
AL230	X	-	-	-	-	-	-	-	-
AL320	X	-	-	-	-	-	-	-	-
AL420	X	-	-	X	-	-	-	-	-
AL430	X	-	-	X	-	-	-	-	-
AL530	-	-	-	X	-	-	-	-	-
GCT 3-14	-	-	X	-	-	-	-	-	-
GCT 3-14 +	-	-	X	-	-	-	-	-	-
MLA 2-25 H	X	-	-	-	-	-	-	-	-
MLA 3-25 H	X	-	-	-	-	-	-	-	-
MLA 3-25 H-C	X	-	-	-	-	-	-	-	-
MLA 4-50 H	X	-	-	X	-	-	-	-	-
MLA 4-50 H-C	X	-	-	X	-	-	-	-	-
MLA 5-50 H	-	-	-	X	-	-	-	-	-
R165	-	-	-	-	-	X	-	-	-
R220	-	-	-	-	-	X	-	-	-
R260	-	-	-	-	-	-	-	X	-
RT105	-	X	X	-	-	-	-	-	-
RT135	-	-	-	X	-	-	-	-	-
RT165	-	-	-	-	-	X	-	-	-
RT185	-	-	-	-	-	-	X	-	-
RT215	-	-	-	-	-	-	-	X	-
ULM 412 H	-	-	X	-	-	-	-	-	-
ULM 412 H	-	-	X	-	-	-	-	-	-
ULM 415 H	-	-	X	-	-	-	-	-	-
ULM 415 H	-	-	X	-	-	-	-	-	-
V210 - NEW	-	-	-	X	-	X	-	-	-
V230 - NEW	-	-	-	-	-	X	-	-	-
V275 - NEW	-	-	-	-	-	X	-	X	-
VT210 - NEW	-	-	-	-	-	-	X	-	-
VT230 - NEW	-	-	-	-	-	-	-	X	-
VT275 - NEW	-	-	-	-	-	-	-	X	-
MLA 1-25 H OLD	X	-	-	-	-	-	-	-	-
MLA 3-35 H OLD	X	-	-	-	-	-	-	-	-
MLA 4-50 H OLD	X	-	-	X	-	-	-	-	-

TABLE SYMBOL				
	No predisposition required		Hydraulic line	 Return piping to hydraulic oil tank

TABLE SYMBOL					
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes