Fiche technique :


STACKY 10 D28




MANITOU
HANDLING YOUR WORLD

	Technical characteristics		Métrique
1.1	Manufacturer		Manitou
1.2	Model Name		Stacky 10 D28
1.3	Power source		Electrical
1.4	Operator type		Pedestrian
1.5	Max. capacity	Q	1000 kg
1.6	Load center of gravity	c	600 mm
1.8	Load distance, centre of drive axle to fork	x	653 mm
1.9	Wheelbase	y	1160 mm
	Weight		
2.1	Overall weight without tools		620 kg
	Wheels		
3.1	Tires type		Polyurethane
3.5.2	Number of drive wheels - Size of drive wheels		1 x 200x80
3.3	Number of load wheels - Size of load wheels		2 x 78x78
3.4	Number of castor wheels		1
3.4	Number of stabilizer wheels / Size of the stabilizer wheels		2 x 125x50
3.5	Number of front wheels / rear wheels		1 / 2
3.6	Front wheel gauge	b10	517 mm
3.7	Rear wheel gauge	b11	421 mm
	Dimensions		
4.2	Mast lowered height	h1	2030 mm
4.5	Mast extended height	h4	3400 mm
4.9	Height tiller min. / max.	h14 / h14	850 mm / 1350 mm
4.15	Fork height in low position	h13	90 mm
4.19	Overall length	l1	1817 mm
4.20	Length to face of forks	l2	667 mm
4.21	Overall width	b1	806 mm
4.22	Forks section / width / length	s / e / l	70 mm x 80 mm / 1150 mm
4.25	Fork spread	b5	560 mm
4.26	Distance between wheel arms/loading surfaces	b4	290 mm
4.24	Fork carriage width	b3	700 mm
4.32	Ground clearance at centre of wheelbase	m2	20 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2234 mm
4.35	Turning radius	Wa	1346 mm
	Performances		
5.1	Travel speed (laden / unladen)		3.50 km/h / 5 km/h
5.2	Lifting speed (laden / unladen)		0.12 m/s / 0.20 m/s
5.3	Lowering speed (laden / unladen)		0.12 m/s / 0.10 m/s
5.7	Gradeability (laden / unladen)		3.50 % / 5 %
5.10	Service brake		Electro magnetic
5.11	Parking brake		Handle Release
	Engine		
6.1	Drive motor rating S2 60 min		0.30 kW
6.2	Lift motor rating at S3 15%		2 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		Semi-Traction
6.4	Battery voltage / capacity		24 V / 85 Ah
6.5	Battery weight (+/- 5%)		50 kg
7.2	Power		0.30 kW
	Miscellaneous		
8.1	Type of drive control		AC
8.4	Sound level at the driver's ear according to DIN 12 053		65 dB

Stacky 10 D28 - Schémas d'encombrement






Caractéristiques des outils


Outil 1 000 kg	Capacité de l'accessoire	Centre de gravité de la charge	A1	A2	B	B1		C	D	E	E1	E2	F	Poids
	kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
EPE 1000	1000	350	700	730	60	-	-	245	-	-	-	-	320	38
FA 1000	1000	500	950	1017	-	190	710	45	80	40	-	-	730	123
FR 1000	1000	600	1150	1182	560	200	320	90	-	70	-	-	700	82
FUT 1000	300	600	795	600	1057	350	650	245	-	240	631	-	-	92
PLF 1000	1000	350	700	727	600	-	-	275	-	91	-	-	630	65
POT 1000	500	600	625	652	50	-	-	145	-	-	-	-	320	33

Outils


EPE 1000




FA 1000




FR 1000




FUT 1000



PLF 1000



POT 1000



Siège Social
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



Cette publication présente le descriptif des versions et possibilités de configuration des produits Manitou qui peuvent différer en équipement. Les équipements présentés dans cette brochure peuvent être de série, en option, ou non disponibles suivant les versions. Manitou se réserve le droit, à tout moment et sans préavis, de modifier les spécifications décrites et représentées. Les spécifications portées n'engagent pas le constructeur. Pour plus de détails, contactez votre concessionnaire Manitou. Document non contractuel. Présentation des produits non contractuelle. Liste des spécifications non exhaustive. Les logos ainsi que l'identité visuelle de l'entreprise sont la propriété de Manitou et ne peuvent être utilisés sans autorisation. Tous droits réservés. Les photos et schémas contenus dans la présente brochure ne sont fournis qu'à des fins de consultation et à titre indicatif.
Manitou BF SA - Société anonyme à conseil d'administration - Capital social : 39 668 399 euros - 857 802 508 RCS Nantes